# **Safety Data Sheet**

Issue Date: 06-Jun-2016 Revision Date: 02-Jun-2018 Version 1

#### 1. IDENTIFICATION

Product Identifier

Product Name Black Vulcanizing Cement - Brush Flammable

Black Vulcanizing Cement - Brush Extra Thick Flammable

Other means of identification

**SDS #** ELG-003

**Product Code** Catalog Numbers: 1-782, 1-783, 1-781, 1-784, 1-785, 2-782, 2-783, 2-781, 2-784, 2-785,

4-782, 4-783, 4-781, 4-784, 4-785

UN/ID No UN1133

Recommended use of the chemical and restrictions on use

Recommended Use Rubber adhesive.

Details of the supplier of the safety data sheet

**Supplier Address** 

ELGI Rubber Company, LLC 600 N. Magnolia Ave. Luling, TX 78648

Ph: 830-875-5539

**Emergency Telephone Number** 

Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America) #79536

## 2. HAZARDS IDENTIFICATION

Appearance Black, high viscosity liquid Physical state Liquid Odor Petrolic

#### Classification

Skin corrosion/irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable Liquids	Category 2

#### **Hazards Not Otherwise Classified (HNOC)**

May be harmful in contact with skin

# Signal Word

Danger

# **Hazard statements**

Causes skin irritation
May cause drowsiness or dizziness
May be fatal if swallowed and enters airways
Highly flammable liquid and vapor



Revision Date: 02-Jun-2018



#### **Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves/protective clothing/eye protection/face protection
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Keep away from heat/sparks/open flames/hot surfaces. — No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Keep cool

# **Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

If skin irritation occurs: Get medical advice/attention

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do not induce vomiting

IN CASE OF FIRE: Use CO2, dry chemical, or foam for extinction

#### **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep container tightly closed

## **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Other hazards

Very toxic to aquatic life with long lasting effects

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%
N-Heptane	142-82-5	85-95
Carbon Black	1333-86-4	0-5

<sup>\*\*</sup>If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.\*\*

## 4. FIRST-AID MEASURES

**First Aid Measures** 

**General Advice** Provide this SDS to medical personnel for treatment.

Eye Contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Revision Date: 02-Jun-2018

**Skin Contact** Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If

skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before

reuse.

**Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not

breathing, give artificial respiration. If symptoms persist, call a physician.

**Ingestion** Do not induce vomiting. Immediately call a poison center or doctor/physician.

Most important symptoms and effects

**Symptoms** Causes skin irritation. May be harmful in contact with skin. May cause pulmonary edema.

Possible symptoms are irritation of the mucous membranes, dry cough and respiratory difficulty. Other symptoms may include dizziness, headache, nausea, and loss of

coordination.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Aspiration of material into the lungs due to vomiting can cause

chemical pneumonitis which can be fatal. Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to high concentrations of hydrocarbon solvents. The use of other drugs with less arrhythmogenic potential should be considered. If sympathomimetic drugs are administered, observe for the development of cardiac

arrhythmias.

#### 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media** 

Water spray (fog). Alcohol resistant foam. Dry chemical. Carbon dioxide (CO2).

Unsuitable Extinguishing Media Do not use solid water streams.

**Specific Hazards Arising from the Chemical** 

Highly flammable liquid and vapor. The liquid vapor may settle into low areas or may travel along the ground or surface to ignition sources where they might ignite or explode. Flash back possible over considerable distance.

Hazardous Combustion Products Carbon monoxide. Carbon dioxide (CO2).

**Explosion Data** 

**Sensitivity to Static Discharge** Take precautionary measures against static discharge.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to keep fire-exposed containers cool. Fight fire remotely due to the risk of explosion.

#### 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

**Personal Precautions** Wear protective clothing as described in Section 8 of this safety data sheet. Evacuate

personnel to safe areas. Remove all sources of ignition. Ensure adequate ventilation. Avoid

Revision Date: 02-Jun-2018

breathing vapors or mists.

#### Environmental precautions

**Environmental precautions** Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See

Section 12, Ecological Information.

#### Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so. Prevent evaporation by covering with

foam. Soak up and contain spill with an inert (i.e. vermiculite, dry sand or earth) absorbent

material.

**Methods for Clean-Up**Use only non-sparking tools. Place in properly labeled, sealed, non-leaking containers.

Dispose of contents/container via a licensed waste disposal contractor. For waste disposal,

see section 13 of the SDS.

#### 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on Safe Handling Wash face, hands, and any exposed skin thoroughly after handling. Wear protective

gloves/protective clothing and eye/face protection. Avoid breathing

dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Ground/bond container and receiving equipment. Ground/bond container and receiving equipment. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static

discharges. Keep cool.

# Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Store locked up. Heat

sensitive-store under inert gas.

**Incompatible Materials** Strong oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## **Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
N-Heptane	STEL: 500 ppm	TWA: 500 ppm	IDLH: 750 ppm
142-82-5	TWA: 400 ppm	TWA: 2000 mg/m <sup>3</sup>	Ceiling: 440 ppm 15 min
		(vacated) TWA: 400 ppm	Ceiling: 1800 mg/m <sup>3</sup> 15 min
		(vacated) TWA: 1600 mg/m <sup>3</sup>	TWA: 85 ppm
		(vacated) STEL: 500 ppm	TWA: 350 mg/m <sup>3</sup>
		(vacated) STEL: 2000 mg/m <sup>3</sup>	
Carbon Black	TWA: 3 mg/m <sup>3</sup> inhalable fraction	TWA: 3.5 mg/m <sup>3</sup>	IDLH: 1750 mg/m <sup>3</sup>
1333-86-4		(vacated) TWA: 3.5 mg/m <sup>3</sup>	TWA: 3.5 mg/m <sup>3</sup>
			TWA: 0.1 mg/m <sup>3</sup> Carbon black in
			presence of Polycyclic aromatic
			hydrocarbons PAH

#### Appropriate engineering controls

**Engineering Controls** Apply technical measures to comply with the occupational exposure limits. Showers

Eyewash stations

Ventilation systems. Explosion-proof general and local exhaust ventilation.

#### Individual protection measures, such as personal protective equipment

**Eye/Face Protection** Wear goggles or chemical safety glasses. Refer to 29 CFR 1910.133 for eye and face

protection regulations.

**Skin and Body Protection** Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal

> technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Refer to 29 CFR 1910.138 for appropriate skin and body protection.

Revision Date: 02-Jun-2018

If necessary, wear a MSHA/NIOSH-approved respirator. Refer to 29 CFR 1910.134 for **Respiratory Protection** 

respiratory protection requirements.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands before

breaks and immediately after handling the product.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

Physical state Liquid

**Appearance** Black, high viscosity liquid Petrolic Odor Color Black **Odor Threshold** Not determined

Remarks • Method **Property** Values

Not determined -90.0 to -90.1 °C / -131.7 to -130.3 **Melting Point/Freezing Point** 

**Boiling Point/Boiling Range** 98.1 to 98.7 °C 208.5 to 209.6 °F

-4.0 °C / 24.8 °F Flash Point

**Evaporation Rate** (butyl acetate = 1)

Flammability (Solid, Gas) Not determined

Flammability Limits in Air Not applicable

**Upper Flammability Limits** 7% **Lower Flammability Limit** 1.1%

**Vapor Pressure** 110.7 hPa (83.0 mmHg) at 37.7  $^{\circ}$  C

(99.9° F), 53.3 hPa (40.0 mmHg) at

20.0 ° C (68.0° F)

**Vapor Density** 3.30 (Air=1)

**Relative Density** 0.684 g/mL at 25° C (77° F)

**Water Solubility** Not determined Solubility in other solvents Insoluble **Partition Coefficient** log Pow > 3.000223.0 °C / 433.4 °F **Auto-ignition Temperature** 

**Decomposition Temperature** Not determined **Kinematic Viscosity** Not determined **Dynamic Viscosity** Not determined **Explosive Properties** Not determined **Oxidizing Properties** Not determined

ELG-003 - Black Vulcanizing Cement - Brush Flammable Black Vulcanizing Cement - Brush Extra Thick Flammable

•

Revision Date: 02-Jun-2018

#### Other Information

Molecular weight 100.2 g/mol

VOC Content (%) N/A

# 10. STABILITY AND REACTIVITY

#### Reactivity

Not reactive under normal conditions.

#### **Chemical Stability**

Stable under recommended storage conditions.

#### Possibility of Hazardous Reactions

None under normal processing.

#### **Conditions to Avoid**

Heat, flames and sparks.

#### **Incompatible Materials**

Strong oxidizing agents.

#### **Hazardous Decomposition Products**

None known based on information supplied.

## 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

**Product Information** 

**Eye Contact** Avoid contact with eyes.

**Skin Contact** Causes skin irritation. May be harmful in contact with skin.

**Inhalation** May cause drowsiness or dizziness. May cause irritation to the mucous membranes and

upper respiratory tract.

**Ingestion** May cause gastrointestinal irritation, nausea, diarrhea, and vomiting.

#### Component Information

Chemical Name	ATEmix (oral)	ATEmix (dermal)	Inhalation LC50
N-Heptane 142-82-5	-	= 3000 mg/kg (Rabbit)	= 103 g/m <sup>3</sup> (Rat) 4 h
Carbon Black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-

# Information on physical, chemical and toxicological effects

**Symptoms** Please see section 4 of this SDS for symptoms.

ELG-003 - Black Vulcanizing Cement - Brush Flammable Black Vulcanizing Cement - Brush Extra Thick Flammable

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity

Carbon black is a possible carcinogen when it appears as a respirable dust.

Revision Date: 02-Jun-2018

Chemical Name	ACGIH	IARC	NTP	OSHA
Carbon Black	A3	Group 2B		X
1333-86-4				

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

**STOT - single exposure** May cause drowsiness or dizziness.

**Aspiration hazard** May be fatal if swallowed and enters airways.

#### **Numerical measures of toxicity**

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal) 3,000.00 mg/kg ATEmix (inhalation-dust/mist) 108.00 mg/L

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

Very toxic to aquatic life with long lasting effects.

#### Component Information

Chemical Name	Algae/aquatic plants	Fish	Crustacea
N-Heptane		375.0: 96 h Cichlid fish mg/L LC50	10: 24 h Daphnia magna mg/L
142-82-5			EC50
Carbon Black			5600: 24 h Daphnia magna mg/L
1333-86-4			EC50

## Persistence/Degradability

Not determined.

#### Bioaccumulation

Not determined.

#### **Mobility**

Chemical Name	Partition Coefficient
N-Heptane	4.66
142-82-5	

#### **Other Adverse Effects**

Not determined

## 13. DISPOSAL CONSIDERATIONS

#### **Waste Treatment Methods**

Disposal of Wastes Whatever cannot be saved for recovery or recycling should be managed in an appropriate

and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance

Revision Date: 02-Jun-2018

with federal, state and local requirements.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

## California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
N-Heptane	Toxic
142-82-5	Ignitable

## 14. TRANSPORT INFORMATION

**Note** Please see current shipping paper for most up to date shipping information, including

exemptions and special circumstances.

DOT

UN/ID No UN1133
Hazard Class 3
Packing Group II

**IATA** 

UN/ID No UN1133
Hazard Class 3
Packing Group II

**IMDG** 

UN/ID No UN1133
Hazard Class 3
Packing Group II
Marine Pollutant Yes

## 15. REGULATORY INFORMATION

#### International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/E LINCS	ENCS	IECSC	KECL	PICCS	AICS
N-Heptane	X	Х	Х	Present	Х	Present	Х	Х
Carbon Black	X	Х	Х	Present	Х	Present	Х	Х

#### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

Revision Date: 02-Jun-2018

#### US Federal Regulations

#### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

#### CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### US State Regulations

## **California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65	
Carbon Black - 1333-86-4	Carcinogen	

#### **U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
N-Heptane 142-82-5	X	X	X
Carbon Black 1333-86-4	X	X	X

# **16. OTHER INFORMATION**

NFPA_	Health Hazards	Flammability	Instability	Special Hazards
	1	3	0	Not determined
HMIS_	Health Hazards	Flammability	Physical hazards	Personal Protection
	1	3	0	Not determined

Issue Date:06-Jun-2016Revision Date:09-Jun-2016Revision Note:New format

#### <u>Disclaimei</u>

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**