



Empack Spraytech Inc.
98 Walker Drive
Brampton, Ontario, L6T 4H6
Canada
905-792-6571

PRODUCT: Emzone Brake & Parts Cleaner Exotic 2.0 - 390 g

CODE: P6-045215

SECTION 01: IDENTIFICATION

Manufacturer..... Empack Spraytech Inc.
Product Item Numbers..... P6-045215
Product Identity..... Emzone Brake & Parts Cleaner Exotic 2.0 - 390 g
24 hour emergency telephone number..... CANUTEC: 1-613-996-6666.
Recommended Use..... Brake cleaner.

SECTION 02: HAZARD IDENTIFICATION



Label Elements:
Signal Word..... DANGER.
Hazard Classification:
Physical Hazards..... Flammable Aerosols - Category 1. Gases Under Pressure - Compressed gas.
Health Hazards..... Acute Toxicity Dermal - Category 5. Acute Toxicity Inhalation - Category 5. Skin Irritation - Category 3. Eye Damage/Irritation - Category 2A. Specific Target Organ Toxicity, Single Exposure - Category 3.
Environmental Hazards..... Not Classified.
Hazard Statement..... H222:Extremely flammable aerosol (1). H229:Pressurized container: may burst if heated (1). H280:Contains gas under pressure; may explode if heated (C). H313:May be harmful in contact with skin . H333:May be harmful if inhaled. H316:Causes mild skin irritation. H319:Causes serious eye irritation. H335:May cause respiratory irritation. H336:May cause drowsiness or dizziness.
Precautionary Statements:
Prevention..... P210:Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211:Do not spray on an open flame or other ignition source. P251:Do not pierce or burn, even after use. P264+P265: Wash hands thoroughly after handling. Do not touch eyes. P280:Wear eye protection/face protection. P261:Avoid breathing dust/fume/gas/mist/vapours/spray. P271:Use only outdoors or in a well-ventilated area.
Response..... P304+P317:IF INHALED: Get medical help. P302+P317: IF ON SKIN: Get medical help. P332+P317:If skin irritation occurs: Get medical help. P305+P351+P338:IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P317: If eye irritation persists: Get medical help.
Storage..... P304+P340:IF INHALED: Remove person to fresh air and keep comfortable for breathing. P319: Get medical help if you feel unwell.
Disposal..... P410+P412:Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F. P403+P233:Store in a well-ventilated place. Keep container tightly closed. P405: Store locked up.
Hazard(s) not otherwise classified (HNOC) Use only as directed.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Liquid Organocarbonate	HMIRA RN Pending	30-60
Acetate	HMIRA RN Pending	30-60
Naphtha (petroleum), hydro-treated light	64742-49-0	5-10
Carbon dioxide	124-38-9	5-10

SECTION 04: FIRST-AID MEASURES

Inhalation..... If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain immediate medical assistance.
Skin Contact..... Remove contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Consult a poison control centre or physician immediately.

PRODUCT: Emzone Brake & Parts Cleaner Exotic 2.0 - 390 g**CODE: P6-045215****SECTION 04: FIRST-AID MEASURES**

Eye Contact..... Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention if irritation persists.

Ingestion..... Do not induce vomiting, get medical attention. Rinse mouth. Obtain medical advice.

Most important symptoms/effects, acute .. Causes serious eye irritation.

and delayed

Indication of immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. In case of shortness of breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media..... Dry chemical powder. Carbon dioxide. Foam, water spray or fog.

Unsuitable Extinguishing Media..... Do not use water jet as an extinguisher, as this will spread the fire.

Specific Hazards Arising from the Chemical Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Special Protective Equipment and Firefighters must use standard protective equipment including flame retardant coat, helmet

Precautions for Firefighters with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

General Fire Hazards..... Extremely flammable aerosol.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective No action shall be taken involving any personal risk or without suitable training. Evacuate

Equipment and Emergency Procedures surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid walking through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 08).

Methods and Materials for Containment .. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see section 13). Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.)

and Cleaning Up away from spilled material.

Environmental Precautions..... Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

SECTION 07: HANDLING AND STORAGE

Precautions for Safe Handling..... Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Avoid contact with eyes, skin, and clothing. Avoid breathing vapour of this product. Avoid contact with skin and eyes. Avoid prolonged exposure. Use in well-ventilated areas.

Conditions for Safe Storage including any Incompatibilities Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C (122°F). Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store away from incompatible materials (see Section 10).

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL NIOSH
Liquid Organocarbonate	Not established	Not established	Not established	Not established	100 ppm
Acetate	200 ppm	250 ppm	200 ppm	250 ppm	TWA 200 ppm (610 mg/m3) ST 250 ppm (760 mg/m3)
Naphtha (petroleum), hydro-treated light	353 ppm	Not available	Not available	Not available	Not available
Carbon dioxide	5000 ppm	30000 ppm	9000 mg/m3	Not available	STEL: 30000ppm; TWA: 5000ppm
Appropriate Engineering Controls.....	Local exhaust ventilation required to maintain the point of use below the Threshold Limit Value if unprotected personnel are involved. Ensure that eyewash stations and safety showers are available.				
Individual Protection Measures:					
Eye/Face Protection.....	Do not get in eyes. Wear safety glasses with side-shields.				

PRODUCT: Emzone Brake & Parts Cleaner Exotic 2.0 - 390 g**CODE: P6-045215****SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

Skin Protection..... Chemical resistant gloves are recommended. Avoid contact with the skin. Wear appropriate chemical resistant clothing.

Respiratory Protection..... Use dust and mist respirator.

Thermal Hazards..... None Known.

General Hygiene Considerations..... When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment prior to use.

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Form..... Aerosol.

Physical Appearance..... Spray mist.

Odor..... Hydrocarbons.

Odor Threshold (ppm)..... Not available.

Specific Gravity 0.980-1.020.

Vapour Pressure (mm Hg)..... Not available.

Vapour Density (Air=1)..... >1.

pH..... Not applicable.

Boiling Point liquid (°C)..... >50.

Melting/Freezing Point (°C)..... Not available.

Flash point, Liquid (°C), Method..... -15.6. (Acetate).

Aerosol Ignition Distance..... Ignition Distance of greater than or equal to 75 cm.

Flashback..... No.

Evaporation Rate (n-Butyl Acetate = 1)..... Not available.

VOC Content..... NMT 10.

Solubility in water..... Slightly soluble.

Auto Ignition Temperature (liquid), °C..... 458. (Liquid Organocarbonate).

Lower Flammable Limit (% Vol)..... 3.1. (Acetate).

Upper Flammable Limit (% Vol)..... 12.9. (Liquid Organocarbonate).

Note..... NMT = Not More Than.

SECTION 10: STABILITY AND REACTIVITY

Reactivity Product not reactive under normal conditions of use.

Chemical Stability..... Material is stable under normal conditions.

Possibility of Hazardous Reactions..... Will not occur.

Conditions to Avoid..... Avoid sources of heat and flame, and electrostatic charge.

Incompatible Materials..... Strong oxidizing agents. Strong acids.

Hazardous Decomposition Products..... Carbon Oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Liquid Organocarbonate	5.36 mg/L (4 hr - rat)	5,000 mg/kg (oral - rat); > 2,000 mg/kg (dermal - rat)
Acetate	49 mg/L (4 hr - rat)	6,482 mg/kg (oral - rat); > 2,000 mg/kg (dermal - rat)
Naphtha (petroleum), hydro-treated light	33-42 mg/L (Rat - 4 hrs)	>5,800 mg/kg (Oral - Rat); >2,920 mg/kg (Dermal - Rabbit)
Carbon dioxide	Not available	Not available
Information on Likely Routes of Exposure:		
Routes of entry - Inhalation.....	Yes.	
Routes of entry - Skin & Eye.....	Yes.	
Routes of entry - Ingestion.....	Yes.	
Routes of entry - Skin Absorption.....	No.	
Symptoms Related to the Physical,	Irritant effects.	
Chemical and Toxicological Characteristics		
Acute Toxicity.....	May be harmful in contact with skin. May be harmful if inhaled.	
Skin Corrosion/Irritation.....	Causes mild skin irritation.	
Serious Eye Damage/Eye Irritation.....	Causes serious eye irritation.	
Respiratory or Skin Sensitization.....	Not classified.	
Germ Cell Mutagenicity.....	Not classified.	
Carcinogenicity.....	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
Reproductive Toxicity.....	Not classified.	
STOT - Single Exposure.....	Specific target organ toxicity single exposure Category 3. May cause drowsiness and dizziness. May cause respiratory irritation.	
STOT - Repeated Exposure.....	Not classified.	

PRODUCT: Emzone Brake & Parts Cleaner Exotic 2.0 - 390 g**CODE: P6-045215****SECTION 11: TOXICOLOGICAL INFORMATION**

Aspiration Hazard..... Not classified.
 Chronic Effects..... No long term chronic effects are known or anticipated.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity..... May be dangerous for the environment. No data is available on the product itself. Should not be released into the environment. This product contains the following substance which may also be hazardous for the environment: Naphtha (CAS # 64742-49-0): Toxicity to fish: LC50 4.1 mg/L, 96 hrs; Toxicity to Daphnia: EC50 10 mg/L, 48 hrs; Toxicity to algae: EC50 11 mg/L, 72 hrs; NOEC 0.1 mg/L, 72 hrs.
 Persistence and degradability The product itself has not been tested.
 Bioaccumulation Potential..... The product itself has not been tested.
 Mobility in Soil..... The product itself has not been tested.
 Other Adverse Effects..... None Known.

SECTION 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods..... Dispose in accordance with local, provincial and federal regulations.

SECTION 14: TRANSPORT INFORMATION

TDG (Canada- Road)..... Limited Quantity (UN1950, AEROSOLS flammable, Class 2.1).
 DOT (US-Road)..... Limited Quantity (UN1950, AEROSOLS flammable, Class 2.1).
 IMDG (International- Marine)..... Limited Quantity (UN1950, AEROSOLS flammable, Class 2.1).
 IATA (International- Air)..... Limited Quantity (UN1950, AEROSOLS flammable, Class 2.1).

SECTION 15: REGULATORY INFORMATION

Canada Regulations:..... Refer to Section 2 for a WHMIS 2015 Classification for this product.
 US Regulations
 California Proposition 65..... This product is not subject to warning labeling under California Proposition 65.

SECTION 16: OTHER INFORMATION

Disclaimer..... The information contained herein is based on data considered accurate. No guarantee or warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. The SDS provider assumes no responsibility for personal injury or property damage to vendors or users or third parties, caused by the material. Such vendors or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR.
 Abbreviations..... ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous Materials Information System STOT: Specific Target Organ Toxicity.
 NFPA Storage Level..... Level 3.
 Prepared by Regulatory Affairs
 Latest Revision 2025-04-03