

Prema Canada Inc.
3230 Mainway Unit 3
Burlington, Ontario, L7M 1A5
Canada
800.268.6311

PRODUCT: Prema Rim Release - 18.9 L

CODE: AD-PR8253

SECTION 01: IDENTIFICATION

Manufacturer..... Empack Spraytech Inc.
Product Item Numbers..... AD-PR8253
Product Identity..... Prema Rim Release - 18.9 L
24 hour emergency telephone number..... CANUTEC: 1-613-996-6666.
Recommended Use..... Dissolves corrosion, scale, and rust as well as preventing damage to parts and penetrating into small spaces.

SECTION 02: HAZARD IDENTIFICATION



Label Elements:
Signal Word..... DANGER.
Hazard Classification:
Physical Hazards..... Flammable Liquids - Category 3.
Health Hazards..... Skin Irritation - Category 2. Eye Damage/Irritation - Category 2A. Carcinogenicity - Category 2. Reproductive Toxicity - Category 2. Specific Target Organ Toxicity, Single Exposure - Category 3. Aspiration Hazard - Category 1.
Environmental Hazards..... Not Classified.
Hazard Statement..... H226:Flammable liquid and vapour. H315:Causes skin irritation. H319:Causes serious eye irritation. H351:Suspected of causing cancer. H361:Suspected of damaging fertility or the unborn child. H335:May cause respiratory irritation. H336:May cause drowsiness or dizziness. H304:May be fatal if swallowed and enters airways.
Precautionary Statements:
Prevention..... P210:Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233:Keep container tightly closed. P240:Ground and bond container and receiving equipment. P241:Use explosion-proof electrical/ventilating/lighting equipment. . P242:Use non-sparking tools. P243:Take action to prevent static discharges. P264+P265: Wash hands thoroughly after handling. Do not touch eyes. P280: Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P203:Obtain, read and follow all safety instructions before use. P261:Avoid breathing dust/fume/gas/mist/vapours/spray. P271:Use only outdoors or in a well-ventilated area.
Response..... P303+P361+P353:IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water. P370+P378:In case of fire: Use CO2, dry chemicals or foam to extinguish. P302+P352:IF ON SKIN: Wash with plenty of water. P332+P317:If skin irritation occurs: Get medical help. P362+P364:Take off contaminated clothing and wash it before reuse. P321:For specific treatment see section 4 on this SDS. P305+P351+P338:IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P317: If eye irritation persists: Get medical help. P318: IF exposed or concerned, get medical advice. . P304+P340:IF INHALED: Remove person to fresh air and keep comfortable for breathing. P319: Get medical help if you feel unwell. P301+P316: IF SWALLOWED: Get emergency medical help immediately. . P331:Do NOT induce vomiting.
Storage..... P403+P235:Store in a well ventilated place. Keep cool. P233:Keep container tightly closed. P405: Store locked up.
Disposal..... P501:Dispose of contents/container in accordance with local, regional, national, and/or international regulations.
Hazard(s) not otherwise classified (HNOC) None Known.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

| CHEMICAL NAME AND SYNONYMS | CAS # | WT. % |
|--|------------|-------|
| Xylene | 1330-20-7 | 30-60 |
| Mineral Spirits | 8052-41-3 | 15-40 |
| Distillates (Petroleum) Hydrotreated Light | 64742-47-8 | 10-30 |
| Ethylbenzene | 100-41-4 | 5-10 |

PRODUCT: Prema Rim Release - 18.9 L

CODE: AD-PR8253

SECTION 04: FIRST-AID MEASURES

| | |
|--|--|
| Inhalation..... | If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain immediate medical assistance. If breathing is difficult, give oxygen and get medical attention. Do not give adrenaline, epinephrine or similar drugs following exposure to this product. |
| Skin Contact..... | Remove contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. If irritation or redness develops consult a poison control centre or physician immediately. |
| Eye Contact..... | Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention if irritation persists. |
| Ingestion..... | Do not induce vomiting, get medical attention. Rinse mouth. Obtain medical advice. |
| Most important symptoms/effects, acute .. and delayed | Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct contact with eyes may cause temporary irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause redness and pain. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. In case of shortness of breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed. |

SECTION 05: FIRE-FIGHTING MEASURES

| | |
|--|---|
| Suitable Extinguishing Media..... | Dry chemical powder. Carbon dioxide. Foam, water spray or fog. |
| Unsuitable Extinguishing Media..... | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific Hazards Arising from the Chemical | None known. |
| Special Protective Equipment and | Firefighters must use standard protective equipment including flame retardant coat, helmet with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. |
| Precautions for Firefighters | |
| General Fire Hazards..... | Flammable liquid and vapour. |

SECTION 06: ACCIDENTAL RELEASE MEASURES

| | |
|--|--|
| Personal Precautions, Protective | No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid walking through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 08). |
| Equipment and Emergency Procedures | |
| Methods and Materials for Containment .. and Cleaning Up | Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see section 13). Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. |
| Environmental Precautions..... | Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination. |

SECTION 07: HANDLING AND STORAGE

| | |
|---|--|
| Precautions for Safe Handling..... | Avoid contact with eyes, skin, and clothing. Avoid breathing vapour of this product. Avoid contact with skin and eyes. Avoid prolonged exposure. Use in well-ventilated areas. |
| Conditions for Safe Storage including any Incompatibilities | Store locked up. Do not handle or store near an open flame, heat or other sources of ignition. Store away from incompatible materials (see Section 10). |

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

| INGREDIENTS | TWA | ACGIH TLV STEL | PEL | OSHA PEL STEL | REL | NIOSH |
|---|--|----------------|---------------------|-----------------|------------------------------------|-----------------|
| Xylene | 50 ppm | 150 ppm | 100 ppm (435 mg/m3) | Not established | Not established | Not established |
| Mineral Spirits | 100 ppm | Not available | 500 ppm | Not available | 350 mg/m3 | |
| Distillates (Petroleum) Hydrotreated Light | 120 mg/m3 | 197 ppm | Not established | Not established | Not established | |
| Ethylbenzene | 100 ppm | 125 ppm | 100 ppm (435 mg/m3) | Not established | 100 ppm (435 mg/m3) / STEL 125 ppm | |
| Appropriate Engineering Controls..... | Local exhaust ventilation required to maintain the point of use below the Threshold Limit Value if unprotected personnel are involved. | | | | | |
| Individual Protection Measures: Eye/Face Protection..... | Do not get in eyes. Wear safety glasses with side-shields. | | | | | |

PRODUCT: Prema Rim Release - 18.9 L

CODE: AD-PR8253

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

Skin Protection..... Chemical resistant gloves are recommended. Avoid contact with the skin. Wear appropriate chemical resistant clothing.

Respiratory Protection..... Use dust and mist respirator.

Thermal Hazards..... None Known.

General Hygiene Considerations..... When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment prior to use.

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Form..... Liquid.

Physical Appearance..... Clear liquid.

Odor..... Hydrocarbons.

Odor Threshold (ppm)..... Not available.

Specific Gravity 0.800-0.860.

Vapour Pressure (psig)..... Not available.

Vapour Density (Air=1)..... >1.

pH..... Not applicable.

Boiling Point liquid (°C)..... >100.

Melting/Freezing Point (°C)..... -42 to -69.

Flash Point (°C), Method..... Not available.

Evaporation Rate (n-Butyl Acetate = 1)..... >1.

VOC Content..... NMT 95.

Solubility in water..... Insoluble.

Aerosol Ignition Distance..... Not applicable.

Flashback..... Not applicable.

Auto Ignition Temperature (°C)..... 464-500. (Xylene).

Lower Flammable Limit (% Vol)..... 1.0. (Xylene).

Upper Flammable Limit (% Vol)..... 7.0. (Xylene).

Note..... NMT = Not More Than.

SECTION 10: STABILITY AND REACTIVITY

Reactivity Product not reactive under normal conditions of use.

Chemical Stability..... Material is stable under normal conditions.

Possibility of Hazardous Reactions..... Will not occur.

Conditions to Avoid..... Avoid sources of heat and flame, and electrostatic charge.

Incompatible Materials..... Strong oxidizing agents. Strong acids.

Hazardous Decomposition Products..... Carbon Oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

| INGREDIENTS | LC50 | LD50 |
|--|-------------------------|--|
| Xylene | 27.6 mg/L (Rat - 4 hrs) | 3,253 mg/kg (Oral - Rat); 12,180 mg/kg (Dermal - Rabbit) |
| Mineral Spirits | 3,500 ppm (Rat - 4hrs) | >5,000 mg/kg (Oral - Rat) |
| Distillates (Petroleum) Hydrotreated Light | >1,400ppm (Rat - 4hrs) | >5,000 mg/kg (Oral - Rat); >3,000 mg/kg (Dermal - Rabbit) |
| Ethylbenzene | 4000 ppm (Rat - 4 hrs) | 3,500 mg/kg (Rat - Oral); 17,800 mg/kg (Dermal - Rabbit) |

Information on Likely Routes of Exposure:

Routes of entry - Inhalation..... No.

Routes of entry - Skin & Eye..... Yes.

Routes of entry - Ingestion..... Yes.

Routes of entry - Skin Absorption..... Yes.

Symptoms Related to the Physical, Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Defatting of the skin. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Acute Toxicity

Skin Corrosion/Irritation..... Causes skin irritation.

Serious Eye Damage/Eye Irritation..... Causes serious eye irritation.

Respiratory or Skin Sensitization..... Not known to be a sensitizer.

Germ Cell Mutagenicity..... No information is available, and no adverse effects are expected.

Carcinogenicity..... Contains: . Ethylbenzene (CAS#: 100-41-4): IARC: Group 2B (Possibly Carcinogenic to Humans); ACGIH: Group A3 (Confirmed Animal carcinogen with unknown relevance to humans).

Reproductive Toxicity..... Suspected of damaging fertility or the unborn child.

PRODUCT: Prema Rim Release - 18.9 L

CODE: AD-PR8253

SECTION 11: TOXICOLOGICAL INFORMATION

STOT - Single Exposure..... Specific target organ toxicity single exposure Category 3. May cause drowsiness and dizziness. May cause respiratory irritation.

STOT - Repeated Exposure..... Not classified.

Aspiration Hazard..... Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.

Chronic Effects..... Organic solvents may be absorbed into the body by inhalation and ingestion and cause permanent damage to the nervous system, including the brain. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity..... May be dangerous for the environment. No data is available on the product itself. Should not be released into the environment. This product contains the following substance which may also be hazardous for the environment: Xylene (CAS#:1330-20-7): Toxicity to fish: 780.0 mg/L, 96 hrs; Toxicity to other aquatic invertebrates: EC50 0.8 mg/L, 48 hrs; Toxicity to algae: EC50 10.0mg/L. Ethylbenzene (CAS#:100-41-4): Toxicity to fish: LC50 4.3mg/L,96hr; Toxicity to aquatic invertebrates: LC50 2.6mg/L,96hr; Toxicity to algae: EC5.0mg/L,96hr.

Persistence and degradability The product itself has not been tested.

Bioaccumulation Potential..... The product itself has not been tested.

Mobility in Soil..... The product itself has not been tested.

Other Adverse Effects..... None Known.

SECTION 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods..... Dispose in accordance with local, provincial and federal regulations.

SECTION 14: TRANSPORT INFORMATION

TDG (Canada- Road)..... UN1993, Flammable liquid n.o.s. (Xylene), Class 3, PG III.

DOT (US-Road)..... UN1993, Flammable liquid n.o.s. (Xylene), Class 3, PG III.

IMDG (International- Marine)..... UN1993, Flammable liquid n.o.s. (Xylene), Class 3, PG III.

IATA (International- Air)..... UN1993, Flammable liquid n.o.s. (Xylene), Class 3, PG III.

Other Information..... ICAO/IATA PI Y344/355/366. Product may ship as LTD QTY if TDG, ICAO/IATA or IMDG Limited Quantity provisions are met.

SECTION 15: REGULATORY INFORMATION

Canada Regulations:..... Refer to Section 2 for a WHMIS 2015 Classification for this product.

Canadian Environmental Protection Act ... (CEPA) All ingredients listed appear on the Domestic Substances List (DSL).

Domestic Substances List (DSL)..... Yes.

US Regulations..... Environmental Protection Act: Constituents of this product are included on the TSCA inventory. OSHA (29CFR 1910.1200). This product is considered hazardous under the OSHA Hazard Communication Standard.

SECTION 16: OTHER INFORMATION

Disclaimer..... The information contained herein is based on data considered accurate. No guarantee or warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. The SDS provider assumes no responsibility for personal injury or property damage to vendors or users or third parties, caused by the material. Such vendors or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

Abbreviations..... ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous Materials Information System STOT: Specific Target Organ Toxicity.

Note..... The VOC content listed in section 9 is as per the interpretation that there is no CARB or ECCC category for this product format - therefore, there is no limit to meet.

Prepared by Regulatory Affairs

Latest Revision 2023-10-11