


Taking Care of Your Tires.

PREMA Products, Inc.

1500 Industrial Blvd., Madison, GA 30650 USA Toll Free: 866-657-7362 | Fax: 770-234-4119 | www.premaproducts.com

PREMA Bias & Radial Nail Hole Repair Chart (Crown Area Only)

Bias Radial Nail Hole Repair Chart Crown Area Only				1- Piece Repair Injury Angle < 25 degrees	2-Piece Repair Injury Angle > 25 degrees		
Tire Type	Injury	y Size mm	Carbide Cutter	Combi / W Pilot Wire	Stem Unit / W Pilot Wire	Universal Repair	Radial Repair
	1/8	3	PCC-1	PC-1	N/A	PUR-1	PR-109
	1/4	6	PCC-2 / PCC-2P	PC-2	PCS-2	PUR-2 / PUS-2	PR-109
	1/4	6	PCC-2	PC-2	PCS-2	PUR-2 / PUS-2	PR-109/110
	5/16	8	PCC-3 / PCC-3P	PC-3	PCS-3	PUR-3 / PUS-3	PR-110/115
00 0	3/8	10	PCC-4	PC-4	PCS-4	PUR-3 / PUS-3	PR-120



Maximum Injury Size: 1/4" (6mm)

Passenger & Light Truck Tires

Maximum Injury Size: 3/8" (10mm)

Medium & Heavy Truck Tires

Any injury exceeding the Maximum Allowable Injury Size, as stated above, will require a section repair to be performed at a Full Service Repair Facility.