

KEX Tire Repair Materials

Product #s: KLD-32 (SKU No. 103000187)

SDS #: RTT-KX-001

Rev. # 7

Rev. Date: Jan 01, 2024

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: KEX Leak Detector

Chemical Family: Aqueous solution containing glycol & organic compounds

Product Use: Tire Leak Detection

Restrictions on Use: Use as directed by manufacturer

Manufacturer: Rema Tip Top North America Inc. 1500 Industrial Blvd. Madison, GA 30650 Phone: 706-752-4000

24-Hour Emergency Phone Number: North America: 800-424-9300 (CHEMTREC) International: 703-527-3887 (CHEMTREC) Collect Calls Accepted

2. HAZARD IDENTIFICATION

GHS Classification

Health Hazards Eye Irritation, Category 2B Specific Target Organ Systemic Toxicity, Single Exposure, Category 3, Respiratory Tract Irritation [Inhalation, Ingestion, Skin absorption]

GHS Labeling Pictograms:



Signal Word: Warning!

Hazard Statements

H320: Causes eye irritation H335: May cause respiratory irritation



KEX Tire Repair Materials

Product #s: KLD-32 (SKU No. 103000187)

SDS #: RTT-KX-001

Rev. # 7

Rev. Date: Jan 01, 2024

Precautionary Statements

Prevention:

P233: Keep container tightly closed.

P261: Avoid breathing vapors.

P264: Wash hands and exposed skin thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear eye protection / face protection.

Response:

P304 + P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

P337 + P313: If eye irritation persists: Get medical advice/attention.

Storage:

P403 + P233: Store in a well-ventilated place. Keep container tightly closed. P405: Store locked up.

Disposal:

P501: Dispose of contents/container in accordance with local/regional/national regulations.

3. <u>COMPOSITION/ INFORMATION ON INGREDIENTS</u>

Chemical characterization

Glycol & Aromatic compounds solution

Component*	CAS #	Weight %
Propylene Glycol	57-55-6	2-10
Sodium Dodecylbenzenesulfonate	68081-81-2	1-6
4,4-Dimethyloxazolidine	51200-87-4	< 1
Sodium Xylenesulfonate	1300-72-7	< 1

4. FIRST AID MEASURES

Inhalation

Symptoms & Effects: Nausea, irritation of the nose and airways, headache, coughing

Measures: Immediately move outdoors or to fresh air. If not breathing or if breathing is difficult, provide artificial respiration or oxygen. If irritation occurs, seek medical attention.



KEX Tire Repair Materials

Product #s: KLD-32 (SKU No. 103000187)

SDS #: RTT-KX-001

Rev. # 7

Rev. Date: Jan 01, 2024

Skin Contact

Symptoms & Effects: Slight skin irritation, burning sensation, redness, swelling, and blisters **Measures:** Wash contaminated areas with mild soap and water after use. Wash contaminated clothing before reuse. If skin irritation occurs, seek medical attention.

Eye Contact

Symptoms & Effects: Eye irritation, stinging sensation, tearing, and redness, and swelling of the eyes. **Measures:** Immediately flush eyes gently with plenty of water for at least 15 minutes. While washing, remove contact lenses if present and easy to do so and continue rinsing. Rinse beneath eyelids by holding eyelids apart with clean fingers while washing. Seek medical attention.

Ingestion

Symptoms & Effects: Stomach or intestinal irritation, nausea, vomiting, abdominal cramps, diarrhea, lumbar pain, dizziness, drowsiness

Measures: Seek immediate medical attention. Do NOT induce vomiting. If awake and alert, rinse mouth and drink 1 glass of water to help dilute the material. Do not give liquids to a drowsy or unconscious person. If vomiting occurs, keep heads below hips to prevent aspiration.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Alcohol-resistant foam, Water spray, Fog, Carbon dioxide, Dry chemical

Unsuitable Extinguishing Media: None identified

Hazardous Combustion Products: Hydrocarbons, Carbon monoxide, Carbon dioxide

Protective Equipment for Fire-Fighters: Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

Precautions for Fire-Fighters: This product does not burn, however heating may release vapors which can be ignited.

6. ACCIDENTAL RELEASE MEASURES

Protective Equipment: Recommended to wear chemical splash goggles & gloves and discard of gloves that show tears, pinholes, or signs of wear. Wear proper garments to reduce skin exposure, such as long-sleeves and pants.

Personal Precautions: Persons not wearing proper PPE should be excluded from the area of contamination until clean-up has been completed. Ensure adequate ventilation.



KEX Tire Repair Materials

Product #s: KLD-32 (SKU No. 103000187)

SDS #: RTT-KX-001 Rev. # 7 Rev. Date: Jan 01, 2024

Environmental Precautions: Do not allow discharge into drains, surface waters, or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained or if material discharges into drains or ground water.

Methods & Materials for Clean-Up: Absorb material with inert materials. Shovel or gather material and place in appropriate container for disposal. Wash spill area thoroughly.

7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation and personal protection. Avoid contact with eyes, skin and clothing. Wear proper personal protective equipment when handling this product. Do not eat, drink or smoke when using this product. Wash hands and face after handling this product and before eating, drinking, and smoking.

Storage: Keep container tightly closed and in a dry, cool and well-ventilated area, away from direct sunlight. Keep away from food, drink, and animal foodstuffs.

Incompatible Materials: Strong oxidizing agents, Strong acids

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits :

Exposure Limits have not been established for this product or any of its components.

Engineering Controls: Use product in a well-ventilated area.

Occupational Exposure Controls: Ensure adequate ventilation, especially in confined areas. Consider all potential hazards of this material, applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting PPE. Ensure that eyewash stations and safety showers are proximal to the work location. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Protective and Hygiene Measures: Wash hands before breaks and after handling product. When using, do not eat, drink, or smoke. In case of clothes contamination, remove and wash contaminated clothing before re-use.

Eye Protection: Recommended to wear face shield or chemical splash goggles when there is potential for the exposure of the eyes to the product. Have a suitable eye wash station or bottle nearby in case of splashing into the eyes.

Hand Protection: Recommended to wear gloves when using this product, and to discard of gloves that show tears, pinholes, or signs of wear.



KEX Tire Repair Materials

Product #s: KLD-32 (SKU No. 103000187)

SDS #: RTT-KX-001 Rev. # 7 Rev. Date: Jan 01, 2024

Skin Protection: Recommended to wear long-sleeved clothing, pants and proper foot covering in order to minimize direct skin contact with the product. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Respiratory Protection: Although unlikely, a NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be appropriate under certain circumstances or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release or other circumstances where an air-purifying respirator may not provide adequate protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Pale liquid **Odor:** Mild Odor Threshold: No data available **pH:** 7 - 8 (Calculated) Melting Point: No data available Freezing point: No data available **Initial boiling point:** No data available Boiling range: 212°F (100°C) Flash point (Tag closed cup): Not applicable **Evaporation rate:** No data available Flammability: Lower Limit: Not applicable Upper Limit: Not applicable Vapor pressure: < 0.1 psi Vapor density: No data available Relative density: 1.0 g/cm³ (8.3 lb/gal) Solubility in water: Completely Soluble Partition coefficient (n-octanol/water): No data available Auto-ignition temperature: No data available Decomposition temperature: No data available Viscosity (dynamic): No data available

10. STABILITY AND REACTIVITY

Reactivity: No decomposition if stored and applied as directed.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Will not react under normal conditions.

Conditions to Avoid: Excessive heat

Incompatible Materials: Strong oxidizing agents, Strong acids Page 5 of 17



KEX Tire Repair Materials

Product #s: KLD-32 (SKU No. 103000187)

SDS #: RTT-KX-001 Rev. # 7	Rev. Date: Jan 01, 2024
----------------------------	-------------------------

Hazardous decomposition products: Hydrocarbons, Carbon monoxide, Carbon dioxide

11. TOXICOLOGICAL INFORMATION

Primary Routes of Exposure: Skin contact, Eye contact, Ingestion, Inhalation

Symptoms Related to Physical, Chemical and Toxicological Characteristics: Nausea, irritation of the nose, throat and airways, dizziness, drowsiness, headache, defatting of the skin, irritation to the digestive tract

Delayed and Immediate Effects & Chronic Effects from Exposure: This material may cause respiratory irritation.

Measures of Toxicity:

Acute toxicities are calculated based on component toxicities Mixture: Acute Oral Toxicity: No data available Acute Dermal Toxicity: No data available Acute Inhalation Toxicity: No data available

Propylene Glycol	CAS # 57-55-6
Acute Oral Toxicity	LD ₅₀ Rat: 20,000 mg/kg
Acute Dermal Toxicity	LD ₅₀ Rat: 20,800 mg/kg
Acute Inhalation Toxicity	No Data Available
4.4 Dimethylovozelidine	CAS # 51200 97 A

4,4-Dimetnyloxazolidine	CAS # 51200-87-4
Acute Oral Toxicity	LD ₅₀ Rat: 1,037 mg/kg
Acute Dermal Toxicity	LD_{50} Rat: > 2,000 mg/kg
Acute Inhalation Toxicity	LC ₅₀ Rate: 1.1 mg/l

Carcinogen Claims:

OSHA: No, International Agency for Research on Cancer (IARC): No; 4 [Probably Not Carcinogenic] ACGIH: No; A5 [Not Suspected], National Toxicology Program (NTP) Report on Carcinogens: No

12. ECOLOGICAL INFORMATION

Eco-toxicity: This substance may be harmful to aquatic organisms. It is strongly advised that this substance does not enter the environment.

Propylene Glycol	CAS # 57-55-6
Toxicity to Fish	LC ₅₀ – 52,930 mg/l (Fathead Minnow; 96 h)
Toxicity to Daphnia	EC ₅₀ -> 10,000 mg/l (Daphnia; 48 h)



KEX Tire Repair Materials

Product #s: KLD-32 (SKU No. 103000187)

SDS #: RTT-KX-001 Rev. #	7 Rev. Date: Jan 01, 2024
--------------------------	---------------------------

4,4-Dimethyloxazolidine	CAS # 51200-87-4
Toxicity to Fish	LC ₅₀ – 95 mg/l (Rainbow Trout; 96 h)
	$LC_{50} - 59$ mg/l (Bluegill Sunfish; 96 h)
Toxicity to Daphnia	EC ₅₀ – 45 mg/l (Daphnia; 48 h)

Persistence & Degradability: No data available **Bio-accumulative Potential:** No data available **Mobility in Soil:** No data available **Other Adverse Effects:** No data available

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with Federal, State or Local regulations. Contaminated packaging should be emptied as far as possible before disposal.

14. TRANSPORT INFORMATION

DOT SHIPPING CLASSIFICATION:

This product is not regulated as a hazardous material for transport.

IMDG (Marine) SHIPPING CLASSIFICATION:

This product is not regulated as a dangerous good for transport.

IATA (Air) SHIPPING CLASSIFICATION:

This product is not regulated as a dangerous good for transport.

15. <u>REGULATORY INFORMATION</u>

All components of this product conform to the following national inventory requirements. US TSCA, EU EINECS and Canada DSL

CANADIAN REGULATIONS

WHMIS 2015 Classification: Same as OSHA GHS Classification.

UNITED STATES REGULATIONS

SARA Title III

Section 302 – Extremely Hazardous Chemicals

The following ingredients are subject to the supplier notification requirements of Section 302 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 37 *None Listed* Page 7 of 17 SDS ID: RTT-KX-001



KEX Tire Repair Materials

Product #s: KLD-32 (SKU No. 103000187)

Section 313 – Toxic Chemicals

The following ingredients are subject to the supplier notification requirements of Section 313 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 37 *None Listed*

OTHER FEDERAL REGULATIONS

Components of this product are subject to RCRA Hazardous Waste requirements. Clean Air Act (CAA) Hazardous Air Pollutants requirements and OSHA Process Safety Management (PSM) high hazard requirements.

STATE REGULATIONS

California Proposition 65

This product does not contain materials known to the state of California to cause cancer, birth defects, and other reproductive harm.

California Hazardous Substances List/Permissible Exposure List California Toxic air contaminants **Connecticut Permissible Exposure Limits** Delaware List of Chemicals and RQs Hawaii Permissible Exposure Limits Idaho Toxic Air Pollutants Illinois Toxic Air Contaminants List Louisiana Toxic Air Pollutants Maine Hazardous Air Pollutants Maryland Toxic Air Pollutants for Existing Sources Massachusetts Hazardous Substances List Michigan Permissible Exposure Limits Minnesota Hazardous Substances Minnesota Permissible Exposure Limits Nebraska Hazardous Air Pollutants New Jersey RTK Hazardous Substances List/TCPA Extremely Hazardous Substances List New York List of Hazardous Substances Ohio Toxic Air Contaminants Oklahoma Toxic Air Contaminants North Carolina TAP Emissions Rates Requiring a Permit Pennsylvania Hazardous Substances List Rhode Island Toxic Air Contaminants **Tennessee Permissible Exposure Limits** Vermont Hazardous Air Contaminants/Permissible Exposure Limits Washington Permissible Exposure Limits for Airborne Contaminants. West Virginia Toxic Air Pollutant List Wisconsin hazardous Air Contaminants



KEX Tire Repair Materials

Product #s: KLD-32 (SKU No. 103000187)

SDS #: RTT-KX-001 Rev. #7 Rev. Date: Jan 01, 2024

Note: Entries under Section 15 are not intended to be all inclusive of Federal and State laws and regulations. Please consult the appropriate agencies for further clarification of any requirements.

16. OTHER INFORMATION

This SDS conforms to the OSHA Hazard Communication Standard 1910.1200 published in the Federal Register March 26, 2012

2. HAZARD IDENTIFICATION

GHS Classification

Health Hazards

Eye Irritation, Category 2B Specific Target Organ Systemic Toxicity, Single Exposure, Category 3, Respiratory Tract Irritation [Inhalation, Ingestion, Skin absorption]

GHS Labeling Pictograms:



Signal Word: Warning!

Hazard Statements

H320: Causes eye irritation H335: May cause respiratory irritation

Precautionary Statements

Prevention:

P233: Keep container tightly closed. P261: Avoid breathing vapors. P264: Wash hands and exposed skin thoroughly after handling. P271: Use only outdoors or in a well-ventilated area. P280: Wear eye protection / face protection.

Response:

P304 + P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Page 9 of 17



KEX Tire Repair Materials

Product #s: KLD-32 (SKU No. 103000187)

SDS #: RTT-KX-001	Rev. # 7	Rev. Date: Jan 01, 2024
$3D3\pi$. INTERA-001		Nev. Dale. Jan 01, 2024

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

P337 + P313: If eye irritation persists: Get medical advice/attention.

Storage:

P403 + P233: Store in a well-ventilated place. Keep container tightly closed. P405: Store locked up.

Disposal:

P501: Dispose of contents/container in accordance with local/regional/national regulations.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Chemical characterization

Glycol & Aromatic compounds solution

Component*	CAS #	Weight %
Propylene Glycol	57-55-6	2-10
Sodium Dodecylbenzenesulfonate	68081-81-2	1-6
4,4-Dimethyloxazolidine	51200-87-4	< 1
Sodium Xylenesulfonate	1300-72-7	< 1

4. FIRST AID MEASURES

Inhalation

Symptoms & Effects: Nausea, irritation of the nose and airways, headache, coughing **Measures:** Immediately move outdoors or to fresh air. If not breathing or if breathing is difficult, provide artificial respiration or oxygen. If irritation occurs, seek medical attention.



KEX Tire Repair Materials

Product #s: KLD-32 (SKU No. 103000187)

SDS #: RTT-KX-001

Rev. # 7

Rev. Date: Jan 01, 2024

Skin Contact

Symptoms & Effects: Slight skin irritation, burning sensation, redness, swelling, and blisters **Measures:** Wash contaminated areas with mild soap and water after use. Wash contaminated clothing before reuse. If skin irritation occurs, seek medical attention.

Eye Contact

Symptoms & Effects: Eye irritation, stinging sensation, tearing, and redness, and swelling of the eyes. **Measures:** Immediately flush eyes gently with plenty of water for at least 15 minutes. While washing, remove contact lenses if present and easy to do so and continue rinsing. Rinse beneath eyelids by holding eyelids apart with clean fingers while washing. Seek medical attention.

Ingestion

Symptoms & Effects: Stomach or intestinal irritation, nausea, vomiting, abdominal cramps, diarrhea, lumbar pain, dizziness, drowsiness

Measures: Seek immediate medical attention. Do NOT induce vomiting. If awake and alert, rinse mouth and drink 1 glass of water to help dilute the material. Do not give liquids to a drowsy or unconscious person. If vomiting occurs, keep heads below hips to prevent aspiration.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Alcohol-resistant foam, Water spray, Fog, Carbon dioxide, Dry chemical

Unsuitable Extinguishing Media: None identified

Hazardous Combustion Products: Hydrocarbons, Carbon monoxide, Carbon dioxide

Protective Equipment for Fire-Fighters: Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

Precautions for Fire-Fighters: This product does not burn, however heating may release vapors which can be ignited.

6. ACCIDENTAL RELEASE MEASURES

Protective Equipment: Recommended to wear chemical splash goggles & gloves and discard of gloves that show tears, pinholes, or signs of wear. Wear proper garments to reduce skin exposure, such as long-sleeves and pants.

Personal Precautions: Persons not wearing proper PPE should be excluded from the area of contamination until clean-up has been completed. Ensure adequate ventilation.



KEX Tire Repair Materials

Product #s: KLD-32 (SKU No. 103000187)

SDS #: RTT-KX-001 Rev. # 7 Rev. Date: Jan 01, 2024

Environmental Precautions: Do not allow discharge into drains, surface waters, or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained or if material discharges into drains or ground water.

Methods & Materials for Clean-Up: Absorb material with inert materials. Shovel or gather material and place in appropriate container for disposal. Wash spill area thoroughly.

7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation and personal protection. Avoid contact with eyes, skin and clothing. Wear proper personal protective equipment when handling this product. Do not eat, drink or smoke when using this product. Wash hands and face after handling this product and before eating, drinking, and smoking.

Storage: Keep container tightly closed and in a dry, cool and well-ventilated area, away from direct sunlight. Keep away from food, drink, and animal foodstuffs.

Incompatible Materials: Strong oxidizing agents, Strong acids

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits :

Exposure Limits have not been established for this product or any of its components.

Engineering Controls: Use product in a well-ventilated area.

Occupational Exposure Controls: Ensure adequate ventilation, especially in confined areas. Consider all potential hazards of this material, applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting PPE. Ensure that eyewash stations and safety showers are proximal to the work location. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Protective and Hygiene Measures: Wash hands before breaks and after handling product. When using, do not eat, drink, or smoke. In case of clothes contamination, remove and wash contaminated clothing before re-use.

Eye Protection: Recommended to wear face shield or chemical splash goggles when there is potential for the exposure of the eyes to the product. Have a suitable eye wash station or bottle nearby in case of splashing into the eyes.

Hand Protection: Recommended to wear gloves when using this product, and to discard of gloves that show tears, pinholes, or signs of wear.



KEX Tire Repair Materials

Product #s: KLD-32 (SKU No. 103000187)

SDS #: RTT-KX-001 Rev. # 7 Rev. Date: Jan 01, 2024

Skin Protection: Recommended to wear long-sleeved clothing, pants and proper foot covering in order to minimize direct skin contact with the product. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Respiratory Protection: Although unlikely, a NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be appropriate under certain circumstances or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release or other circumstances where an air-purifying respirator may not provide adequate protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Pale liquid **Odor:** Mild Odor Threshold: No data available **pH:** 7 - 8 (Calculated) Melting Point: No data available Freezing point: No data available **Initial boiling point:** No data available Boiling range: 212°F (100°C) Flash point (Tag closed cup): Not applicable **Evaporation rate:** No data available Flammability: Lower Limit: Not applicable Upper Limit: Not applicable Vapor pressure: < 0.1 psi Vapor density: No data available Relative density: 1.0 g/cm³ (8.3 lb/gal) Solubility in water: Completely Soluble Partition coefficient (n-octanol/water): No data available Auto-ignition temperature: No data available Decomposition temperature: No data available Viscosity (dynamic): No data available

10. STABILITY AND REACTIVITY

Reactivity: No decomposition if stored and applied as directed.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Will not react under normal conditions.

Conditions to Avoid: Excessive heat

Incompatible Materials: Strong oxidizing agents, Strong acids Page 13 of 17



KEX Tire Repair Materials

Product #s: KLD-32 (SKU No. 103000187)

SDS #: RTT-KX-001 Rev. # 7	Rev. Date: Jan 01, 2024
----------------------------	-------------------------

Hazardous decomposition products: Hydrocarbons, Carbon monoxide, Carbon dioxide

11. TOXICOLOGICAL INFORMATION

Primary Routes of Exposure: Skin contact, Eye contact, Ingestion, Inhalation

Symptoms Related to Physical, Chemical and Toxicological Characteristics: Nausea, irritation of the nose, throat and airways, dizziness, drowsiness, headache, defatting of the skin, irritation to the digestive tract

Delayed and Immediate Effects & Chronic Effects from Exposure: This material may cause respiratory irritation.

Measures of Toxicity:

Acute toxicities are calculated based on component toxicities Mixture: Acute Oral Toxicity: No data available Acute Dermal Toxicity: No data available Acute Inhalation Toxicity: No data available

Propylene Glycol	CAS # 57-55-6
Acute Oral Toxicity	LD ₅₀ Rat: 20,000 mg/kg
Acute Dermal Toxicity	LD ₅₀ Rat: 20,800 mg/kg
Acute Inhalation Toxicity	No Data Available
4.4 Dimethylovozelidine	CAS # 51200 97 A

4,4-Dimetnyloxazolidine	CAS # 51200-87-4
Acute Oral Toxicity	LD ₅₀ Rat: 1,037 mg/kg
Acute Dermal Toxicity	LD_{50} Rat: > 2,000 mg/kg
Acute Inhalation Toxicity	LC ₅₀ Rate: 1.1 mg/l

Carcinogen Claims:

OSHA: No, International Agency for Research on Cancer (IARC): No; 4 [Probably Not Carcinogenic] ACGIH: No; A5 [Not Suspected], National Toxicology Program (NTP) Report on Carcinogens: No

12. ECOLOGICAL INFORMATION

Eco-toxicity: This substance may be harmful to aquatic organisms. It is strongly advised that this substance does not enter the environment.

Propylene Glycol	CAS # 57-55-6
Toxicity to Fish	LC ₅₀ – 52,930 mg/l (Fathead Minnow; 96 h)
Toxicity to Daphnia	EC ₅₀ -> 10,000 mg/l (Daphnia; 48 h)



KEX Tire Repair Materials

Product #s: KLD-32 (SKU No. 103000187)

SDS #: RTT-KX-001	Rev. # 7	Rev. Date: Jan 01, 2024
		,

4,4-Dimethyloxazolidine	CAS # 51200-87-4
Toxicity to Fish	LC ₅₀ – 95 mg/l (Rainbow Trout; 96 h)
	$LC_{50} - 59$ mg/l (Bluegill Sunfish; 96 h)
Toxicity to Daphnia	EC ₅₀ – 45 mg/l (Daphnia; 48 h)

Persistence & Degradability: No data available **Bio-accumulative Potential:** No data available **Mobility in Soil:** No data available **Other Adverse Effects:** No data available

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with Federal, State or Local regulations. Contaminated packaging should be emptied as far as possible before disposal.

14. TRANSPORT INFORMATION

DOT SHIPPING CLASSIFICATION:

This product is not regulated as a hazardous material for transport.

IMDG (Marine) SHIPPING CLASSIFICATION:

This product is not regulated as a dangerous good for transport.

IATA (Air) SHIPPING CLASSIFICATION:

This product is not regulated as a dangerous good for transport.

15. <u>REGULATORY INFORMATION</u>

All components of this product conform to the following national inventory requirements. US TSCA, EU EINECS and Canada DSL

CANADIAN REGULATIONS

WHMIS 2015 Classification: Same as OSHA GHS Classification.

UNITED STATES REGULATIONS

SARA Title III

Section 302 – Extremely Hazardous Chemicals

The following ingredients are subject to the supplier notification requirements of Section 302 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 37 *None Listed* Page 15 of 17 SDS ID: RTT-KX-001



KEX Tire Repair Materials

Product #s: KLD-32 (SKU No. 103000187)

SDS #: RTT-KX-001	Rev. # 7	Rev. Date: Jan 01, 2024
-------------------	----------	-------------------------

Section 313 – Toxic Chemicals

The following ingredients are subject to the supplier notification requirements of Section 313 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 37 *None Listed*

OTHER FEDERAL REGULATIONS

Components of this product are subject to RCRA Hazardous Waste requirements. Clean Air Act (CAA) Hazardous Air Pollutants requirements and OSHA Process Safety Management (PSM) high hazard requirements.

STATE REGULATIONS

California Proposition 65

This product does not contain materials known to the state of California to cause cancer, birth defects, and other reproductive harm.

California Hazardous Substances List/Permissible Exposure List California Toxic air contaminants **Connecticut Permissible Exposure Limits** Delaware List of Chemicals and RQs Hawaii Permissible Exposure Limits Idaho Toxic Air Pollutants Illinois Toxic Air Contaminants List Louisiana Toxic Air Pollutants Maine Hazardous Air Pollutants Maryland Toxic Air Pollutants for Existing Sources Massachusetts Hazardous Substances List Michigan Permissible Exposure Limits Minnesota Hazardous Substances Minnesota Permissible Exposure Limits Nebraska Hazardous Air Pollutants New Jersey RTK Hazardous Substances List/TCPA Extremely Hazardous Substances List New York List of Hazardous Substances Ohio Toxic Air Contaminants Oklahoma Toxic Air Contaminants North Carolina TAP Emissions Rates Requiring a Permit Pennsylvania Hazardous Substances List Rhode Island Toxic Air Contaminants **Tennessee Permissible Exposure Limits** Vermont Hazardous Air Contaminants/Permissible Exposure Limits Washington Permissible Exposure Limits for Airborne Contaminants. West Virginia Toxic Air Pollutant List Wisconsin hazardous Air Contaminants



KEX Tire Repair Materials

Product #s: KLD-32 (SKU No. 103000187)

SDS #: RTT-KX-001 Rev. # 7 Rev. Da

Rev. Date: Jan 01, 2024

Note: Entries under Section 15 are not intended to be all inclusive of Federal and State laws and regulations. Please consult the appropriate agencies for further clarification of any requirements.

16. OTHER INFORMATION

This SDS conforms to OSHA HazCom 2012 ad WHMIS 2015.

MEDICAL EMERGENCIES:

Call CHEMTREC 24 hours a Day for emergency information

FOR ANY OTHER INFORMATION:

REMA TIP TOP NORTH AMERICA INC. 1500 Industrial Blvd. Madison, GA 30650 706-752-4000

NOTICE: KEX TIRE REPAIR believes that the information contained on this safety data sheet is accurate. The suggested procedures are based on experience as of the date of publication. They are not necessarily all-inclusive, nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of, applicable laws, regulations, rules or insurance requirements.

NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE.