



Safety Data Sheet

REMA Tire Repair Materials

Product #: 77

SDS #: RTT-TRM-033

Rev. #7

Rev. Date 12/14/2023

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Pneumatic Tool Lubricant (Moisture Guard)
Chemical Family : Petroleum Distillates (Hydrocarbons)

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Lubricant
Restrictions on use : Use as directed by manufacturer

1.3. Supplier

Rema Tip Top/North America, Inc
1500 Industrial Blvd. 1500 Industrial Blvd.
Madison, GA 30650
USA
T 706-752-4000

1.4. Emergency telephone number

Emergency number : 800-424-9300 (ChemTrec)- North America
703-527-3887 (ChemTrec) – International (Collect Calls Accepted)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Not classified

2.2. GHS Label elements, including precautionary statements

GHS US labeling

No labeling applicable

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : None known.

2.4. Unknown acute toxicity (GHS US)

No additional information available



Safety Data Sheet

REMA Tire Repair Materials

Product #:77

SDS #: RTT-TRM-O33

Rev. #7

Rev. Date 12/14/2023

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Distillates (petroleum), hydrotreated heavy paraffinic	CAS-No.: 64742-54-7	0 – 100
Distillates (petroleum), solvent - dewaxed heavy paraffinic	CAS-No.: 64742-65-0	0 – 100
Distillates (petroleum), hydrotreated light paraffinic	CAS-No.: 64742-55-8	0 – 100
Distillates (petroleum), solvent-dewaxed light paraffinic	CAS-No.: 64742-56-9	0 – 100

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: No particular/specific measures required.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or a doctor.
First-aid measures after skin contact	: Wash skin with mild soap and water. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution. Get medical attention if irritation develops and persists.
First-aid measures after ingestion	: Rinse mouth with water. Do not induce vomiting. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: No adverse effects expected.
Inhalation	: No adverse effects expected under normal conditions of use. Inhalation of mists or vapors at elevated temperatures may cause respiratory irritation.
Skin	: None under normal use. Repeated or prolonged skin contact may cause dermatitis and defatting.
Eyes	: May cause minor eye irritation.
Ingestion	: Ingestion may cause nausea, vomiting and diarrhea. Irritation to the digestive tract.
Chronic symptoms	: None known.

4.3. Immediate medical attention and special treatment, if necessary

None under normal conditions. Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.



Safety Data Sheet

REMA Tire Repair Materials

Product #:77

SDS #: RTT-TRM-O33

Rev. #7

Rev. Date 12/14/2023

Unsuitable extinguishing media : Use of heavy stream of water may spread fire.

5.2. Specific hazards arising from the chemical

Fire hazard : This product is not classified as flammable or combustible. Could burn but does not ignite readily.
Hazardous decomposition products in case of fire : Toxic fumes may be released. Hydrocarbon. Carbon oxides (CO, CO₂).

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Cool down the containers exposed to heat with a water spray.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with eyes, skin and clothing. Do not touch or walk on the spilled product.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up : Absorb and/or contain spill with inert material, then place in suitable container.
Other information : Dispose of materials or solid residues at an authorized site. Report spill as required by local and federal regulations.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Avoid contact with eyes. Avoid repeated or prolonged skin contact.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.



Safety Data Sheet

REMA Tire Repair Materials

Product #:77

SDS #: RTT-TRM-O33

Rev. #7

Rev. Date 12/14/2023

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.
Incompatible materials : Strong oxidizers. Strong acids. Strong bases.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Pneumatic Tool Lubricant (Moisture Guard)

No additional information available

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

USA - ACGIH - Occupational Exposure Limits

Local name	Mineral oil, excluding metal working fluids Pure, highly and severely refined
ACGIH OEL TWA	5 mg/m ³ (I - Inhalable particulate matter)
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2021

USA - OSHA - Occupational Exposure Limits

Local name	Oil mist, mineral
OSHA PEL (TWA)	5 mg/m ³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

Distillates (petroleum), solvent - dewaxed heavy paraffinic (64742-65-0)

USA - ACGIH - Occupational Exposure Limits

Local name	Mineral oil, excluding metal working fluids Pure, highly and severely refined
ACGIH OEL TWA	5 mg/m ³ (I - Inhalable particulate matter)
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2021

USA - OSHA - Occupational Exposure Limits

Local name	Oil mist, mineral
OSHA PEL (TWA)	5 mg/m ³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)

No additional information available



Safety Data Sheet

REMA Tire Repair Materials

Product #:77

SDS #: RTT-TRM-033

Rev. #7

Rev. Date 12/14/2023

Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)

USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA : 5 mg/m³ inhalable

USA - OSHA - Occupational Exposure Limits

OSHA PEL (TWA) : 5 mg/m³

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

None under normal conditions. Protective gloves recommended.

Eye protection:

Not required for normal conditions of use

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In operations where exposure limits are exceeded or exposure levels are excessive, an approved respirator should be used. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

Thermal hazard protection:

Not applicable.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Amber Liquid.
Color : Amber
Odor : Mild odor petroleum
Odor threshold : No data available
pH : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : No data available
Flash point : ≈ 396 °F
Relative evaporation rate (butyl acetate=1) : No data available
Flammability (solid, gas) : Not applicable.



Safety Data Sheet

REMA Tire Repair Materials

Product #:77

SDS #: RTT-TRM-033

Rev. #7

Rev. Date 12/14/2023

Vapor pressure	:	No data available
Relative vapor density at 20°C	:	No data available
Relative density	:	0.867
Solubility	:	Insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity, kinematic	:	> 21 – < 24 mm ² /s @40C
Viscosity, dynamic	:	No data available
Explosion limits	:	No data available
Explosive properties	:	None.
Oxidizing properties	:	None.

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Strong oxidizers. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	:	Not classified
Acute toxicity (dermal)	:	Not classified
Acute toxicity (inhalation)	:	Not classified



Safety Data Sheet

REMA Tire Repair Materials

Product #: 77

SDS #: RTT-TRM-033

Rev. #7

Rev. Date 12/14/2023

Pneumatic Tool Lubricant (Moisture Guard)	
ATE US (oral)	2019.2 mg/kg
ATE US (dermal)	4523 mg/kg
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 2000 mg/kg body weight
LD50 dermal rabbit	> 5000 mg/kg Source: IUCLID
LC50 Inhalation - Rat	> 5000 mg/m ³
Distillates (petroleum), solvent - dewaxed heavy paraffinic (64742-65-0)	
LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
LD50 oral rat	> 5000 mg/kg body weight OECD 401
LD50 dermal rabbit	> 2000 mg/kg Source: EHCA
LC50 Inhalation - Rat (Dust/Mist)	> 2.18 mg/l Source: ECHA

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified. This product does not contain any component that is considered a carcinogen by IARC, ACGIH, OSHA or NTP.
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: > 21 – < 24 mm ² /s @40C
Symptoms/effects	: No adverse effects expected.
Inhalation	: No adverse effects expected under normal conditions of use. Inhalation of mists or vapors at elevated temperatures may cause respiratory irritation.
Skin	: None under normal use. Repeated or prolonged skin contact may cause dermatitis and defatting.
Eyes	: May cause minor eye irritation.
Ingestion	: Ingestion may cause nausea, vomiting and diarrhea. Irritation to the digestive tract.
Chronic symptoms	: None known.



Safety Data Sheet

REMA Tire Repair Materials

Product #: 77

SDS #: RTT-TRM-O33

Rev. #7

Rev. Date 12/14/2023

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Pneumatic Tool Lubricant (Moisture Guard)

LC50 - Fish [1]	> 100 mg/l Pimephales promelas (Fathead minnow)
EC50 - Other aquatic organisms [1]	> 10000 mg/l Daphnia magna (Water flea)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LC50 - Fish [1]	≥ 100 mg/l
EC50 - Crustacea [1]	> 10000 ml/l
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)

LC50 - Fish [1]	> 5000 mg/l Source: IUCLID
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID

Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)

LC50 - Fish [1]	> 100 mg/l
EC50 - Crustacea [1]	> 10000
ErC50 algae	> 100 mg/l
NOEC chronic crustacea	10 mg/l

12.2. Persistence and degradability

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)

Not rapidly degradable

Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)

Not rapidly degradable

12.3. Bioaccumulative potential

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
---	------------------------

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)

Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
---	------------------------



Safety Data Sheet

REMA Tire Repair Materials

Product #: 77

SDS #: RTT-TRM-033

Rev. #7

Rev. Date 12/14/2023

Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)

Partition coefficient n-octanol/water (Log Pow)	3.9 – 6 Source: IUCLID
---	------------------------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation : Dispose of in accordance with applicable federal, state, and local regulations.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
Not regulated for transport			
14.2. Proper Shipping Name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

14.6. Special precautions for user

DOT
Not regulated

TDG
Not regulated



Safety Data Sheet

REMA Tire Repair Materials

Product #:77

SDS #: RTT-TRM-O33

Rev. #7

Rev. Date 12/14/2023

IMDG
Not regulated

IATA
Not regulated

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Pneumatic Tool Lubricant (Moisture Guard)

SARA Section 311/312 Hazard Classes	Refer to Section 2 for OSHA Hazard Classification.
-------------------------------------	--

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

Pneumatic Tool Lubricant (Moisture Guard)

All chemical substances in this product are listed in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm



Safety Data Sheet

REMA Tire Repair Materials

Product #:77

SDS #: RTT-TRM-033

Rev. #7

Rev. Date 12/14/2023

SECTION 16: Other information

According to 29CFR 1910.1200 OSHA Hazard Communication Standard and the Hazardous Products Regulation (WHMIS 2015)

Data Sources

: This safety data sheet was compiled with data and information from the following sources:
RTECS, ECOSAR, HSDB, SIDS SIAP, CESAR, CHEMICAL DB.

MEDICAL EMERGENCIES:

Call CHEMTREC 24 hours a
Day for emergency information
800-424-9300

FOR ANY OTHER INFORMATION:

REMA TIP TOP/NORTH AMERICA, INC
240 Pegasus Avenue, 2nd floor
NORTHVALE, NJ 07647
201-256-8200

NOTICE: REMA TIP TOP NORTH AMERICA believes that the information contained on this safety data sheet is accurate. The suggested procedures are based on experience as of the date of publication. They are not necessarily all-inclusive, nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of, applicable laws, regulations, rules or insurance requirements.

NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE.

Indication of changes:

new version.

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.