Product Identifier: Skid[™] Penetrating Lubricant Stock Number: B790 Date of the latest revision of the safety data sheet: 09-05-2022 Supercedes:

1 Identification	
(a) Product Identifier:	Skid [™] Penetrating Lubricant
Stock Number:	B790
(b) Other means of identification:	
Synonyms:	None Known
(c) Recommended use and restrictions or	nuse:
Recommended use:	Penetrant
	Lubricant
Restrictions on use:	Uses not described above.
(d) Initial Supplier Identifier:	Myers Tire Supply
Manufacture/Distributor:	1293 S. Main Street
	Akron, OH 44301
Tel No.:	1 (330) 253-5592
Email:	customerservice@stonersolutions.com
(e) Emergency telephone number and any restrictions on the use of that number, if applicable:	1-800-424-9300 [CHEMTREC]

2 Hazard identification

(a) Classification of the hazardous product, namely the appropriate category or subcategory of the hazard class identified in Subparts 2 to 19 of Part 7 or Subparts 1 to 11 of Part 8, or a name that is its substantive equivalent, or for Subpart 20 of Part 7 and Subpart 12 of Part 8, the category of the hazard class or a description of the identified hazard: Germ Cell Mutagenicity Category 1B Carcinogenicity Category 1A Aspiration Hazard Category 1 Skin Corrosion/Irritation Category 2 Serious Eye Damage/Eye Irritation Category 2A Reproductive Toxicity Category2 Specific Target Organ SystemicToxicity (STOT) - Repeated Exposure Category 2 Flammable Liquid Category 3 Specific Target Organ Toxicity Single ExposureCategory 3

(b) Information elements referred to in section 3 of Annex 3 of the GHS and in paragraphs 3(1)(d) to (f) of these Regulations for each of those categories or subcategories. If the required information element is a symbol, either the name of the symbol or the symbol itself may be used:

GHS Hazard class symbols:



Signal word: Hazard statements: Danger Flammable liquid and vapour; May be fatal if swallowed and enters

Product Identifier: Skid[™] Penetrating Lubricant Stock Number: B790 Date of the latest revision of the safety data sheet: 09-05-2022 Supercedes:

	airways; Causes skin irritation; Causes serious eye irritation; May cause
	drowsiness or dizziness; May cause genetic defects.; May cause cancer.;
	Suspected of damaging fertility or the unborn child.; May cause damage
	to organs through prolonged or repeated exposure
ecautionary statements:	
Prevention:	Obtain special instructions before use. Do not handle until all safety
	precautions have been read and understood. Keep away from
	heat/sparks/open flames/hot surfaces. No smoking. Ground/bond
	container and receiving equipment. Use explosion-proof
	[electrical/ventilating/lighting] equipment. Use only non-sparking tools.
	Take precautionary measures against static discharge. Do not breathe
	dust/fume/gas/mist/vapours/spray.Wash thoroughly after handling. Use
	only outdoors or in a well-ventilated area. Wear protective
	gloves/protective clothing/eye protection/face protection.
Response:	IF SWALLOWED: Immediately call a POISON CENTER/doctor. If on skin:
	Wash with plenty of water. IF ON SKIN (or hair): Take off immediately all
	contaminated clothing. Rinse skin with water/shower.IF INHALED:
	Remove victim to fresh air and keep at rest in a position comfortable for
	breathing. IF IN EYES: Rinse cautiously with water for several minutes.
	Remove contact lenses, if present and easy to do. Continue rinsing. IF
	exposed or concerned: Get medical advice/ attention. Call a POISON
	CENTER/doctor if you feel unwell. Specific treatment (see on this label).
	Do NOT induce vomiting. If skin irritation occurs: Get medical
	advice/attention. If eye irritation persists: Get medical advice/attention.
	Take off contaminated clothingand wash it before reuse. In case of fire:
	Use an approprate extinguisher (see section 5) to extinguish.
Storage:	Store in a well-ventilated place. Keep container tightly closed. Store in a
	well-ventilated place. Keep cool. Store locked up.
Disposal:	Dispose of contents/container to a suitable disposal site in accordance
	with local/national/international regulations.

(c) Other hazards known to the supplier with respect to the hazardous product:

Physical hazards not otherwise	None Known
classified	

Health hazards not otherwise classified None Known

3 Composition/information on ingredients				
Chemical Name	Common name and synonyms	CAS registry number and any unique	Concentration]

Product Identifier: Skid[™] Penetrating Lubricant Stock Number: B790 Date of the latest revision of the safety data sheet: 09-05-2022 Supercedes:

		identifiers	
Xylene	None Known	1330-20-7	10 - 30
Solvent naphtha	None Known	64742-96-7	1-20
(petroleum), heavy aliph.			
Distillates (petroleum),	None Known	64742-47-8	1-20
hydrotreated light			
Stoddard solvent	None Known	Mixture	1-20
Ethyl benzene	None Known	100-41-4	3 - 7
Petroleum hydrocarbon	None Known	64742-47-8	1 - 5
Organic oil	None Known	8002-09-3	0.5 - 1.5
Trimethylbenzene 1,2,4-	None Known	95-63-6	0.5 - 1.5
Naphthalene	None Known	91-20-3	0.5 - 1.5
Trimethybenzene	None Known	25551-13-7	0.5 - 1.5
Cumene	None Known	98-82-8	0.1- 0.99
Benzene	None Known	71-43-2	0.1- 0.99

4 First-aid measures

(a) A description of necessary first aid measures, subdivided according to the different routes of exposure (inhalation, ingestion, skin and eye contact):

Inhalation:	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep the victim warm and quiet. Seek immediate medical attention.
Eye contact:	Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.
Skin Contact:	Wash clothing before reuse. Seek medical attention if symptoms persist. In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes.
Ingestion:	Aspiration into the lungs can cause serious damage. Contact a physician, medical facility, or poison control center immediately. Have victim drink 8 to 10 ounces of water to dilute the material in the stomach. Do not induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs.
(b) The most important symptoms and effects, whether acute or delayed:	May be fatal if swallowed and enters airways Causes skin irritation Causes serious eye irritation May cause drowsiness or dizziness May cause damage to organs through prolonged or repeated exposure
(c) An indication of immediate medical attention and special treatment needed, if necessary:	This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: This material is

Product Identifier: Skid[™] Penetrating Lubricant Stock Number: B790 Date of the latest revision of the safety data sheet: 09-05-2022 Supercedes:

> an aspiration hazard. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Inhalation of high concentrations of the material, or one of it's components, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material.

5 Fire-fighting measures

(a) Suitable and unsuitable	
extinguishing media:	
Suitable extinguishing media:	Use CO2, foam or dry chemical.
Unsuitable extinguishing media:	No data available
(b) Specific hazards arising from the	This product contains a component(s) that is considered a flammable
hazardous product, such as the nature	liquid, which has vapors that are heavier than air and may travel along
of any hazardous combustion:	the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. In extreme fire conditions this material may present a floating fire hazard.
(c) Special protective equipment and	Use CO2, foam or dry chemical. Do not direct a solid stream of water or
precautions for firefighters:	foam into hot burning pools, this may cause frothing and increase fire intensity. Water is generally not effective and may spread fire; however, water spray may be used from a safe distance to cool closed containers and protect surrounding area. Fire fighters should wear normal protective equipment and positive-pressure self-contained breathing apparatus.
6 Accidental release measures	

(a) Personal precautions, protective equipment and emergency procedures:(b) Methods and materials for containment and cleaning up:

No data available

If runoff occurs, notify authorities as required. Ventilate contaminated area. Remove all sources of ignition. Place absorbent materials into container and close it tightly. Dispose of container properly. Clean up with absorbent material. Avoid run-off into storm sewers and ditches which may lead to natural waterways. Stop or reduce discharge if it can be done safely. Wear appropriate personal protective equipment (PPE).

7 Handling and storage

(a) Precautions for safe handling: Use bonding and grounding when transferring quantities of material. Normal precautions common to safe manufacturing practice should be

Product Identifier: Skid[™] Penetrating Lubricant Stock Number: B790 Date of the latest revision of the safety data sheet: 09-05-2022 Supercedes:

	followed in handling and storage. Wash hands thoroughly after handling.
	Avoid contact with eyes. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death. Use with adequate ventilation. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of vapor. Do not use near ignition sources.
(b) Conditions for safe storage, including any incompatibilities:	
Conditions for safe storage:	Empty container may contain residues which are hazardous. Keep away from heat, sparks and flame. Store in a cool, dry, well ventilated area away from all sources of ignition.
Materials to Avoid/Chemical Incompatibility:	No data available

8 Exposure controls/personal protection

(a) Control parameters, including occupational exposure limit values or biological limit values and the source of those values:

Chemical Name	Occupational Exposure Limits -	Occupational Exposure Limits -	Occupational Exposure Limits -
	TWAs	STELs	Ceiling
Xylene	100 PPM TWA; 434	150 PPM STEL; 651	No data available
	MG/M3 TWA	MG/M3 STEL	
Solvent naphtha (petroleum), heavy aliph.	No data available	No data available	No data available
Distillates (petroleum), hydrotreated light	No data available	No data available	No data available
Stoddard solvent	No data available	No data available	No data available
Ethyl benzene	100 PPM TWA; 434	543 MG/M3 STEL; 125	No data available
	MG/M3 TWA	PPM STEL	
Petroleum hydrocarbon	No data available	No data available	No data available
Organic oil	No data available	No data available	No data available
Trimethylbenzene 1,2,4-	123 MG/M3 TWA; 25 PPM TWA	No data available	No data available
Naphthalene	10 PPM TWA; 52	79 MG/M3 STEL; 15	No data available
	MG/M3 TWA	PPM STEL	
Trimethybenzene	25 PPM TWA; 123	No data available	No data available
-	MG/M3 TWA		
Cumene	No data available	No data available	No data available
Benzene	3.2 MG/M3 TWA; 1	16 MG/M3 STEL; 5	No data available

Product Identifier: Skid[™] Penetrating Lubricant Stock Number: B790 Date of the latest revision of the safety data sheet: 09-05-2022 Supercedes:

	PPM TWA	PPM STEL	
Canada – British Columbia– Occupational Exposure Limits:			

Occupational Occupational Occupational **Chemical Name Exposure Limits -Exposure Limits -Exposure Limits -**Ceiling **TWAs** STELS **Xylene** 100 PPM TWA 150 PPM STEL No data available Solvent naphtha (petroleum), No data available No data available No data available heavy aliph. Distillates (petroleum), 200 MG/M3 TWA No data available No data available hydrotreated light Stoddard solvent No data available No data available No data available 100 PPM TWA Ethyl benzene 125 PPM STEL No data available Petroleum hydrocarbon No data available No data available No data available Organic oil No data available No data available No data available Trimethylbenzene 1,2,4-25 PPM TWA No data available No data available Naphthalene No data available 10 PPM TWA 15 PPM STEL Trimethybenzene 25 PPM TWA No data available No data available Cumene No data available No data available No data available Benzene 0.5 PPM TWA 2.5 PPM STEL No data available

Canada – Manitoba – Occupational Exposure Limits:

	Occupational	Occupational	Occupational
Chemical Name	Exposure Limits -	Exposure Limits -	Exposure Limits -
	TWAs	STELs	Ceiling
Xylene	No data available	No data available	No data available
Solvent naphtha (petroleum), heavy aliph.	No data available	No data available	No data available
Distillates (petroleum), hydrotreated light	No data available	No data available	No data available
Stoddard solvent	No data available	No data available	No data available
Ethyl benzene	No data available	No data available	No data available
Petroleum hydrocarbon	No data available	No data available	No data available
Organic oil	No data available	No data available	No data available
Trimethylbenzene 1,2,4-	No data available	No data available	No data available
Naphthalene	No data available	No data available	No data available
Trimethybenzene	No data available	No data available	No data available
Cumene	No data available	No data available	No data available
Benzene	No data available	No data available	No data available

Canada – New Brunswick – Occupational Exposure Limits:

	Occupational	Occupational	Occupational
Chemical Name	Exposure Limits -	Exposure Limits -	Exposure Limits -

Product Identifier: Skid[™] Penetrating Lubricant Stock Number: B790 Date of the latest revision of the safety data sheet: 09-05-2022 Supercedes:

	TWAs	STELs	Ceiling
Xylene	No data available	No data available	No data available
Solvent naphtha (petroleum),	No data available	No data available	No data available
heavy aliph.			
Distillates (petroleum),	No data available	No data available	No data available
hydrotreated light			
Stoddard solvent	No data available	No data available	No data available
Ethyl benzene	No data available	No data available	No data available
Petroleum hydrocarbon	No data available	No data available	No data available
Organic oil	No data available	No data available	No data available
Trimethylbenzene 1,2,4-	No data available	No data available	No data available
Naphthalene	No data available	No data available	No data available
Trimethybenzene	No data available	No data available	No data available
Cumene	No data available	No data available	No data available
Benzene	No data available	No data available	No data available

Canada – Newfoundland & Labrador – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Xylene	No data available	No data available	No data available
Solvent naphtha (petroleum), heavy aliph.	No data available	No data available	No data available
Distillates (petroleum), hydrotreated light	No data available	No data available	No data available
Stoddard solvent	No data available	No data available	No data available
Ethyl benzene	No data available	No data available	No data available
Petroleum hydrocarbon	No data available	No data available	No data available
Organic oil	No data available	No data available	No data available
Trimethylbenzene 1,2,4-	No data available	No data available	No data available
Naphthalene	No data available	No data available	No data available
Trimethybenzene	No data available	No data available	No data available
Cumene	No data available	No data available	No data available
Benzene	No data available	No data available	No data available

Canada – Northwest Territories – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Xylene	No data available	No data available	No data available
Solvent naphtha (petroleum), heavy aliph.	No data available	No data available	No data available
Distillates (petroleum),	No data available	No data available	No data available

Product Identifier: Skid[™] Penetrating Lubricant Stock Number: B790 Date of the latest revision of the safety data sheet: 09-05-2022 Supercedes:

hydrotreated light			
Stoddard solvent	No data available	No data available	No data available
Ethyl benzene	No data available	No data available	No data available
Petroleum hydrocarbon	No data available	No data available	No data available
Organic oil	No data available	No data available	No data available
Trimethylbenzene 1,2,4-	No data available	No data available	No data available
Naphthalene	No data available	No data available	No data available
Trimethybenzene	No data available	No data available	No data available
Cumene	No data available	No data available	No data available
Benzene	No data available	No data available	No data available

Canada – Nova Scotia – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Xylene	No data available	No data available	No data available
Solvent naphtha (petroleum), heavy aliph.	No data available	No data available	No data available
Distillates (petroleum), hydrotreated light	No data available	No data available	No data available
Stoddard solvent	No data available	No data available	No data available
Ethyl benzene	No data available	No data available	No data available
Petroleum hydrocarbon	No data available	No data available	No data available
Organic oil	No data available	No data available	No data available
Trimethylbenzene 1,2,4-	No data available	No data available	No data available
Naphthalene	No data available	No data available	No data available
Trimethybenzene	No data available	No data available	No data available
Cumene	No data available	No data available	No data available
Benzene	No data available	No data available	No data available

Canada – Nunavut – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Xylene	No data available	No data available	No data available
Solvent naphtha (petroleum), heavy aliph.	No data available	No data available	No data available
Distillates (petroleum), hydrotreated light	No data available	No data available	No data available
Stoddard solvent	No data available	No data available	No data available
Ethyl benzene	No data available	No data available	No data available
Petroleum hydrocarbon	No data available	No data available	No data available
Organic oil	No data available	No data available	No data available

Product Identifier: Skid[™] Penetrating Lubricant Stock Number: B790 Date of the latest revision of the safety data sheet: 09-05-2022 Supercedes:

Trimethylbenzene 1,2,4-	No data available	No data available	No data available
Naphthalene	No data available	No data available	No data available
Trimethybenzene	No data available	No data available	No data available
Cumene	No data available	No data available	No data available
Benzene	No data available	No data available	No data available

Canada – Ontario – Occupational Exposure Limits:

	Occupational	Occupational Exposure Limits -	Occupational
Chemical Name	Exposure Limits -		Exposure Limits -
	TWAs	STELs	Ceiling
Xylene	No data available	No data available	No data available
Solvent naphtha (petroleum),	No data available	No data available	No data available
heavy aliph.			
Distillates (petroleum),	No data available	No data available	No data available
hydrotreated light			
Stoddard solvent	No data available	No data available	No data available
Ethyl benzene	100 PPM TWA; 435	125 PPM STEL; 540	No data available
	MG/M3 TWA	MG/M3 STEL	
Petroleum hydrocarbon	No data available	No data available	No data available
Organic oil	No data available	No data available	No data available
Trimethylbenzene 1,2,4-	No data available	No data available	No data available
Naphthalene	52 MG/M3 TWA; 10	15 PPM STEL; 78	No data available
	PPM TWA	MG/M3 STEL	
Trimethybenzene	No data available	No data available	No data available
Cumene	No data available	No data available	No data available
Benzene	0.5 PPM TWA	2.5 PPM STEL	No data available

Canada – Prince Edward Island – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Xylene	No data available	No data available	No data available
Solvent naphtha (petroleum), heavy aliph.	No data available	No data available	No data available
Distillates (petroleum), hydrotreated light	No data available	No data available	No data available
Stoddard solvent	No data available	No data available	No data available
Ethyl benzene	No data available	No data available	No data available
Petroleum hydrocarbon	No data available	No data available	No data available
Organic oil	No data available	No data available	No data available
Trimethylbenzene 1,2,4-	No data available	No data available	No data available
Naphthalene	No data available	No data available	No data available

Product Identifier: Skid[™] Penetrating Lubricant Stock Number: B790 Date of the latest revision of the safety data sheet: 09-05-2022 Supercedes:

Trimethybenzene	No data available	No data available	No data available
Cumene	No data available	No data available	No data available
Benzene	No data available	No data available	No data available

Canada – Quebec – Occupational Exposure Limits:

	Occupational	Occupational Exposure Limits -	Occupational
Chemical Name	Exposure Limits -		Exposure Limits -
	TWAEVs	STEVs	Ceiling
Xylene	100 PPM TWA; 434	150 PPM STEL; 651	No data available
	MG/M3 TWA	MG/M3 STEL	
Solvent naphtha (petroleum),	No data available	No data available	No data available
heavy aliph.			
Distillates (petroleum),	No data available	No data available	No data available
hydrotreated light			
Stoddard solvent	No data available	No data available	No data available
Ethyl benzene	434 MG/M3 TWA; 100	125 PPM STEL; 543	No data available
	PPM TWA	MG/M3 STEL	
Petroleum hydrocarbon	No data available	No data available	No data available
Organic oil	No data available	No data available	No data available
Trimethylbenzene 1,2,4-	123 MG/M3 TWA; 25 PPM TWA	No data available	No data available
Naphthalene	52 MG/M3 TWA; 10	15 PPM STEL; 79	No data available
	PPM TWA	MG/M3 STEL	
Trimethybenzene	25 PPM TWA; 123	No data available	No data available
-	MG/M3 TWA		
Cumene	No data available	No data available	No data available
Benzene	1 PPM TWA; 3 MG/M3	15.5 MG/M3 STEL; 5	No data available
	TWA	PPM STEL	

Canada – Saskatchewan – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Xylene	No data available	No data available	No data available
Solvent naphtha (petroleum), heavy aliph.	No data available	No data available	No data available
Distillates (petroleum), hydrotreated light	No data available	No data available	No data available
Stoddard solvent	No data available	No data available	No data available
Ethyl benzene	No data available	No data available	No data available
Petroleum hydrocarbon	No data available	No data available	No data available
Organic oil	No data available	No data available	No data available
Trimethylbenzene 1,2,4-	No data available	No data available	No data available

Product Identifier: Skid[™] Penetrating Lubricant Stock Number: B790 Date of the latest revision of the safety data sheet: 09-05-2022 Supercedes:

Naphthalene	No data available	No data available	No data available
Trimethybenzene	No data available	No data available	No data available
Cumene	No data available	No data available	No data available
Benzene	No data available	No data available	No data available

Canada - Yukon – Occupational Exposure Limits:

Chemical Name	Occupational Exposure Limits - TWAs	Occupational Exposure Limits - STELs	Occupational Exposure Limits - Ceiling
Xylene	No data available	No data available	No data available
Solvent naphtha (petroleum), heavy aliph.	No data available	No data available	No data available
Distillates (petroleum), hydrotreated light	No data available	No data available	No data available
Stoddard solvent	No data available	No data available	No data available
Ethyl benzene	No data available	No data available	No data available
Petroleum hydrocarbon	No data available	No data available	No data available
Organic oil	No data available	No data available	No data available
Trimethylbenzene 1,2,4-	No data available	No data available	No data available
Naphthalene	No data available	No data available	No data available
Trimethybenzene	No data available	No data available	No data available
Cumene	No data available	No data available	No data available
Benzene	No data available	No data available	No data available

Chemical Name	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL	IDLH
Xylene	No data available	434 MG/M3	150 PPM STEL;	No data available
		TWA; 100 PPM	651 MG/M3 STEL	
		TWA		
Solvent naphtha (petroleum),	No data available	No data available	No data available	No data available
heavy aliph.				
Distillates (petroleum),	No data available	No data available	No data available	No data available
hydrotreated light				
Stoddard solvent	No data available	No data available	No data available	No data available
Ethyl benzene	No data available	20 PPM TWA	No data available	No data available
Petroleum hydrocarbon	No data available	No data available	No data available	No data available
Organic oil	No data available	No data available	No data available	No data available
Trimethylbenzene 1,2,4-	No data available	123 MG/M3	No data available	No data available
		TWA; 25 PPM		
		TWA		
Naphthalene	No data available	10 PPM TWA; 52	15 PPM STEL; 79	No data available
		MG/M3 TWA	MG/M3 STEL	
Trimethybenzene	No data available	123 MG/M3	No data available	No data available

Product Identifier: Skid[™] Penetrating Lubricant Stock Number: B790 Date of the latest revision of the safety data sheet: 09-05-2022 Supercedes:

		TWA; 25 PPM		
		TWA		
Cumene	No data available	No data available	No data available	No data available
Benzene	No data available	1.6 MG/M3 TWA;	2.5 PPM STEL; 8	No data available
		0.5 PPM TWA	MG/M3 STEL	
(b) Appropriate engineering controls	exceeded. No exposure l Ventilation sh	should be used in an imits exist for the cor ould be adequate to ow in this section of t erse effects).	nstituents of this pro prevent exposures a	duct. bove the limits
(c) Individual protection measures, s	uch as personal prot	ective equipment:		
Respiratory Protection:	the product m used if ventila respiratory irr	proved respirator wh hist, spray or aerosol. tion is not sufficient itation develops belo approved nuisance c	A supplied air respir to maintain exposure w the recommended	ator should be e limits. If d exposure limits,

Eye and face protection:	Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Have an eye wash station available.
Skin Protection:	The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.
Hand protection:	No data available
Other protective equipment:	No data available
General hygiene conditions:	Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling.

9 Physical and chemical properties

(a) Appearance, such as physical state and colour:	
Physical state:	Bulk liquid
Colour:	Light amber
(b) Odour:	Aromatic
	Petroleum solvent
	Slight
(c) Odour threshold:	No data available
(d) pH:	Not applicable
(c) Odour threshold:	Petroleum solvent Slight No data available

Product Identifier: Skid[™] Penetrating Lubricant Stock Number: B790 Date of the latest revision of the safety data sheet: 09-05-2022 Supercedes:

(e) Melting point and freezing point:	No data available
(f) Initial boiling point and boiling range	No data available
(°C):	
(g) Flash point (°C):	33
(h) Evaporation rate:	Not determined
(i) Flammability, in the case of solids	No data available
and gases:	
(j) Upper and lower flammability or	
explosive limits:	
Upper flammable or explosive limit,	7
% in air:	
Lower flammable or explosive limit,	0.5
% in air:	
(k) Vapour pressure:	No data available
(l) Vapour density:	>1
(m) Relative density:	0.88
(n) Solubility:	Not determined
(o) Partition coefficient — n-	No data available
octanol/water:	
(p) Auto-ignition temperature (°C):	-32
(q) Decomposition temperature (°C):	No data available
(r) Viscosity:	No data available

10 Stability and reactivity

 (a) Reactivity: (b) Chemical stability: (c) Possibility of hazardous reactions: (d) Conditions to avoid, including static discharge, shock or vibration: 	No data available Stable. No data available Open flames and high temperatures. Strong acids. Strong bases. Hypochlorites. Chlorine. Strong oxidizing agents. Avoid contact with: Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces. No data available
(f) Hazardous decomposition products:	Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Aldehydes. Various hydrocarbons. Alcohols. Ethers. Ketones. Polymer fragments. Carbon Monoxide.

11 Toxicological information

Description of the various toxic health effects and the data used to identify those effects:

Product Identifier: Skid[™] Penetrating Lubricant Stock Number: B790 Date of the latest revision of the safety data sheet: 09-05-2022 Supercedes:

(a) Information on the likely routes of exposure (inhalation, ingestion, skin	Skin Eye
and eye contact):	
(b) Symptoms related to the physical,	May be fatal if swallowed and enters airways Causes skin irritation Causes
chemical and toxicological	serious eye irritation May cause drowsiness or dizziness May cause
characteristics:	damage to organs through prolonged or repeated exposure
	nronic effects from short-term and long-term exposure:
Immediate effects from short term expos	
Inhalation Toxicity:	No data available
Skin Contact:	This material is estimated to be slightly irritating (Primary Irritation Index is 0.5 - 3.0 [rabbits]). Can cause severe irritation. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use. Prolonged or repeated exposure may dry the skin. Symptoms may include redness, discomfort, drying and cracking, or rash. Skin contact may cause irritation.
Eye Contact:	Classification is based on pH and the components listed in Section 3.
Ingestion Toxicity:	No data available
Delayed and chronic effects from long ter	m exposure:
Sensitization:	No data available
Mutagenicity:	No data available
Carcinogenicity:	Based on available information, this material cannot be classified with reguard to carcinogenicity. A component in this material has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain. THIS PRODUCT CONTAINS NO COMPONENTS LISTED AS CARCINOGENIC BY IARC, NTP, OR OSHA 1910(Z)
STOT-single exposure:	Based on available data, the classification criteria are not met.
STOT-repeated exposure:	Classification has been based on toxicological information of the components in Section 3.
Aspiration hazard:	Classification has been based on toxicological information of the components in Section 3.
(d) Numerical measures of toxicity, includ	ling ATEs

(d) Numerical measures of toxicity, including ATEs

Information on toxicological effects: Acute toxicity:

12 Ecological information

(a) Ecotoxicity (aquatic and terrestrial, if No data available available):

Product Identifier: Skid[™] Penetrating Lubricant Stock Number: B790 Date of the latest revision of the safety data sheet: 09-05-2022 Supercedes:

cological Toxicity Data:				
Chemical Name	CAS registry number and any unique identifiers	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
Xylene	1330-20-7	Aquatic LC50 (24h) Daphnia 100 - 1000 MG/L	Code:	Aquatic LC50 (96h) MINNOW 24 - 30 MG/L
Distillates (petroleum), hydrotreated light	64742-47-8	48HR EL50 Daphnia 1.4 MG/L	72HR EL50 Algae 1 MG/L	96HR LL50 Rainbow Trout 2 MG/L
NJ Trade Secret Registry	# 80100382-5110P	48HR EC50 Daphnia = 26 MG/L	IC50-16HR Bacteria = 19000 MG/L	Aquatic LC50 (96h) MINNOW = 20 - 65 MG/L
Ethyl benzene	100-41-4	48HR EC50 Daphnia = 9.55 MG/L	72HR EC50 Algae 4.9 MG/L	Aquatic LC50 (96h) Rainbow Trout = 8.4 MG/L
NJ Trade Secret Registry Organic oil	8002-09-3	48HR EC50 Daphnia 24 MG/L	72HR EC50 Algae > 15 MG/L	Aquatic LC50 (96h) Rainbow Trout 18 MG/L
Trimethylbenzene 1,2,4-	95-63-6	No data available	No data available	Aquatic LC50 (96h) MINNOW = 7.19 - 8.28 MG/L
Naphthalene	91-20-3	48HR EC50 Daphnia = 1.09 - 3.4 MG/L	No data available	Aquatic LC50 (96h) Rainbow Trout = 0.91 - 2.82 MG/L
Trimethybenzene	25551-13-7	No data available	No data available	Aquatic LC50 (96h) MINNOW = 7.19 - 8.28 MG/L
n-Hexane	110-54-3	No data available	No data available	96H LC50 PIMEPHALES PROMELAS 970 ul/l 48H LC50 PIMEPHALES PROMELAS 70 ul/l 96H EC50 PIMEPHALES PROMELAS 950 ul/l
Benzene	71-43-2	No data available	No data available	NRH NR ONCORHYNCHUS

MYKISS 0.00028

ONCORHYNCHUS MYKISS 23.2 ul/l

ul/l NRH NR

Product Identifier: Skid[™] Penetrating Lubricant Stock Number: B790 Date of the latest revision of the safety data sheet: 09-05-2022 Supercedes:

(b) Persistence and degradability:	No data available.	
(c) Bioaccumulative potential:	No data available	
(d) Mobility in soil:	No data available	
(e) Other adverse effects:	No data available	

13 Disposal considerations

Information on safe handling for disposal and methods of disposal, including any contaminated packaging: Spent or discarded material is a hazardous waste.

14 Transport information

-	
Transportation of Dangerous Goods by lan	d (TDG):
(a) UN number:	UN1268
(b) United Nations proper shipping	Petroleum distillates, n.o.s. (contains Xylene)
name as provided for in the United	
Nations Model Regulations:	
(c) Transport hazard class as provided in	3
the United Nations Model Regulations:	
(d) Packing group as provided in the	III
United Nations Model Regulations:	
International carriage of dangerous goods	by sea (IMDG/IMO):
(a) UN number:	UN1268
(b) United Nations proper shipping	Petroleum distillates, n.o.s. (contains Xylene)
name as provided for in the United	
Nations Model Regulations:	
(c) Transport hazard class as provided in	3
the United Nations Model Regulations:	
(d) Packing group as provided in the	111
United Nations Model Regulations:	
International carriage of dangerous goods	
(a) UN number:	UN1268
(b) United Nations proper shipping	Petroleum distillates, n.o.s. (contains Xylene)
name as provided for in the United	
Nations Model Regulations:	
(c) Transport hazard class as provided in	3
the United Nations Model Regulations: (d) Packing group as provided in the	ш
United Nations Model Regulations:	11
Onited Nations Model Regulations.	
(e) Environmental hazards according to	No data available
the International Maritime Dangerous	
Goods Code and the United Nations	

Product Identifier: Skid[™] Penetrating Lubricant Stock Number: B790 Date of the latest revision of the safety data sheet: 09-05-2022 Supercedes:

Model Regulations:	
(f) Transport in bulk (according to	No data available
Annex II of the International	
Convention for the Prevention of	
Pollution From Ships, 1973, as modified	
by the Protocol of 1978 (MARPOL	
73/78) and the International Code for	
the Construction and Equipment of	
Ships carrying Dangerous Chemicals in	
Bulk (IBC Code)):	
(g) Special precautions in connection	No data available
with transport or conveyance either	
within or outside the premises:	

15 Regulatory information

Safety, health and environmental regulations, made within or outside Canada, specific to the product in question: Canada - Domestic Substances List (DSL):

Chemical Name	CAS No	Canada - Domestic Substances List (DSL)
Xylene	1330-20-7	Yes
Solvent naphtha	64742-96-7	Yes
(petroleum), heavy aliph.	04742-90-7	163
Distillates (petroleum),	64742-47-8	Yes
hydrotreated light	04742-47-0	Tes
Stoddard solvent	Mixture	Yes
Ethyl benzene	100-41-4	Yes
Petroleum hydrocarbon	64742-47-8	Yes
Organic oil	8002-09-3	Yes
Trimethylbenzene 1,2,4-	95-63-6	Yes
Naphthalene	91-20-3	Yes
Trimethybenzene	25551-13-7	Yes
Cumene	98-82-8	Yes
Benzene	71-43-2	Yes

Canada - Non-Domestic Substances List (NDSL):

Chemical Name	CAS No	Canada - Non-Domestic Substances List (NDSL)
Xylene	1330-20-7	No
Solvent naphtha	64742-96-7	No
(petroleum), heavy aliph.	04742-90-7	NO

Product Identifier: Skid[™] Penetrating Lubricant Stock Number: B790 Date of the latest revision of the safety data sheet: 09-05-2022 Supercedes:

Distillates (petroleum),	64742-47-8	No
hydrotreated light	04742-47-0	NO
Stoddard solvent	Mixture	No
Ethyl benzene	100-41-4	No
Petroleum hydrocarbon	64742-47-8	No
Organic oil	8002-09-3	No
Trimethylbenzene 1,2,4-	95-63-6	No
Naphthalene	91-20-3	No
Trimethybenzene	25551-13-7	No
Cumene	98-82-8	No
Benzene	71-43-2	No

Canada - Controlled Drugs and Substances:

Chemical Name	CAS No	Schedule I	Schedule II	Schedule III	Schedule IV	Schedule V	Schedule VII	Schedule VIII
Xylene	1330-20-7	No	No	No	No	No	No	No
Solvent naphtha (petroleum), heavy aliph.	64742-96- 7	No	No	No	No	No	No	No
Distillates (petroleum),	64742-47-	No	No	No	No	No	No	No
hydrotreated light	8	NO	NO	NO				INO
Stoddard solvent	Mixture	No	No	No	No	No	No	No
Ethyl benzene	100-41-4	No	No	No	No	No	No	No
Petroleum hydrocarbon	64742-47- 8	No	No	No	No	No	No	No
Organic oil	8002-09-3	No	No	No	No	No	No	No
Trimethylbenzene	95-63-6	No	No	No	No	No	No	No
1,2,4-	33-03-0	NO	NO	NO	NO		NO	NO
Naphthalene	91-20-3	No	No	No	No	No	No	No
Trimethybenzene	25551-13- 7	No	No	No	No	No	No	No
Cumene	98-82-8	No	No	No	No	No	No	No
Benzene	71-43-2	No	No	No	No	No	No	No

Product Identifier: Skid[™] Penetrating Lubricant Stock Number: B790 Date of the latest revision of the safety data sheet: 09-05-2022 Supercedes:

Chemical Name	CAS No	Class A Precursors	Class B Precursors	Exempt Precursors	Class 1 Targeted Substances	Class 2 Targeted Substances
Xylene	1330-20-7	No	No	No	No	No
Solvent naphtha (petroleum), heavy aliph.	64742-96- 7	No	No	No	No	No
Distillates (petroleum), hydrotreated light	64742-47- 8	No	No	No	No	No
Stoddard solvent	Mixture	No	No	No	No	No
Ethyl benzene	100-41-4	No	No	No	No	No
Petroleum hydrocarbon	64742-47- 8	No	No	No	No	No
Organic oil	8002-09-3	No	No	No	No	No
Trimethylbenzene 1,2,4-	95-63-6	No	No	No	No	No
Naphthalene	91-20-3	No	No	No	No	No
Trimethybenzene	25551-13- 7	No	No	No	No	No
Cumene	98-82-8	No	No	No	No	No
Benzene	71-43-2	No	No	No	No	No

Canada - CEPA - Schedule III Export Control List:

Chemical Name	CAS No	Part 1 Prohibited Substances	Part 2 Substances Subject to Notification or Consent	Part 3 Restricted Substances	Export Control List
Xylene	1330-20-7	No	No	No	No
Solvent naphtha (petroleum), heavy aliph.	64742-96- 7	No	No	No	No
Distillates (petroleum), hydrotreated light	64742-47- 8	No	No	No	No
Stoddard solvent	Mixture	No	No	No	No
Ethyl benzene	100-41-4	No	No	No	No
Petroleum hydrocarbon	64742-47- 8	No	No	No	No

Product Identifier: Skid[™] Penetrating Lubricant Stock Number: B790 Date of the latest revision of the safety data sheet: 09-05-2022 Supercedes:

Organic oil	8002-09-3	No	No	No	No
Trimethylbenzene	95-63-6	No	No	No	No
1,2,4-					
Naphthalene	91-20-3	No	No	No	No
Trimethybenzene	25551-13-	No	No	No	No
Timethybenzene	7	NO	NO	NO	NO
Cumene	98-82-8	No	No	No	No
Benzene	71-43-2	No	No	No	No

Canada CEPA - 2015 Greenhouse Gases (GHG) Subject to Mandatory Reporting:

Chemical Name	CAS No	Canada CEPA - 2015 Greenhouse Gases (GHG) Subject to Mandatory Reporting		
Xylene	1330-20-7	No		
Solvent naphtha (petroleum), heavy aliph.	64742-96-7	No		
Distillates (petroleum), hydrotreated light	64742-47-8	Νο		
Stoddard solvent	Mixture	No		
Ethyl benzene	100-41-4	No		
Petroleum hydrocarbon	64742-47-8	No		
Organic oil	8002-09-3	Νο		
Trimethylbenzene 1,2,4-	95-63-6	No		
Naphthalene	91-20-3	No		
Trimethybenzene	25551-13-7	No		
Cumene	98-82-8	No		
Benzene	71-43-2	No		

Canada - Narcotic Control Regulations (C.R.C., c. 1041):

Chemical Name	CAS No	Canada - Narcotic Control Regulations (C.R.C., c. 1041)		
Xylene	1330-20-7	No		
Solvent naphtha	64742-96-7	No		
(petroleum), heavy aliph.	04742-90-7	No		
Distillates (petroleum),	64742-47-8	Νο		
hydrotreated light	04/42-4/-0	NO		
Stoddard solvent	Mixture	No		
Ethyl benzene	100-41-4	No		
Petroleum hydrocarbon	64742-47-8	No		

Product Identifier: Skid™ Penetrating Lubricant Stock Number: B790 Date of the latest revision of the safety data sheet: 09-05-2022 Supercedes:

Organic oil	8002-09-3	No
Trimethylbenzene 1,2,4-	95-63-6	No
Naphthalene	91-20-3	No
Trimethybenzene	25551-13-7	No
Cumene	98-82-8	No
Benzene	71-43-2	No

Canada - Ontario - Toxics Reduction - List of Priority Toxics:

Chemical Name	CAS No	Canada - Ontario - Toxics Reduction - List of Priority Toxics
Xylene	1330-20-7	No
Solvent naphtha	64742.06.7	NI-
(petroleum), heavy aliph.	64742-96-7	Νο
Distillates (petroleum),	64742-47-8	No
hydrotreated light	04/42-4/-0	
Stoddard solvent	Mixture	No
Ethyl benzene	100-41-4	No
Petroleum hydrocarbon	64742-47-8	No
Organic oil	8002-09-3	No
Trimethylbenzene 1,2,4-	95-63-6	No
Naphthalene	91-20-3	No
Trimethybenzene	25551-13-7	No
Cumene	98-82-8	No
Benzene	71-43-2	No

Stockholm Convention on Persistent Organic Pollutants:

Chemical Name	CAS No	Stockholm Convention on Persistent Organic Pollutants
Xylene	1330-20-7	No
Solvent naphtha	64742-96-7	Νο
(petroleum), heavy aliph.	04742-90-7	
Distillates (petroleum),	64742-47-8	Νο
hydrotreated light	04742-47-8	NO
Stoddard solvent	Mixture	No
Ethyl benzene	100-41-4	No
Petroleum hydrocarbon	64742-47-8	No
Organic oil	8002-09-3	No
Trimethylbenzene 1,2,4-	95-63-6	No

Product Identifier: Skid[™] Penetrating Lubricant Stock Number: B790 Date of the latest revision of the safety data sheet: 09-05-2022 Supercedes:

Naphthalene	91-20-3	No
Trimethybenzene	25551-13-7	No
Cumene	98-82-8	No
Benzene	71-43-2	No

Rotterdam Convention on the Prior Informed Consent Procedure for Certain Hazardous Chemicals and Pesticides in International Trade:

Chemical Name	CAS No	Rotterdam Convention on the Prior Informed Consent Procedure for Certain Hazardous Chemicals and Pesticides in International Trade.
Xylene	1330-20-7	No
Solvent naphtha (petroleum), heavy aliph.	64742-96-7	No
Distillates (petroleum), hydrotreated light	64742-47-8	Νο
Stoddard solvent	Mixture	No
Ethyl benzene	100-41-4	No
Petroleum hydrocarbon	64742-47-8	No
Organic oil	8002-09-3	Νο
Trimethylbenzene 1,2,4-	95-63-6	No
Naphthalene	91-20-3	No
Trimethybenzene	25551-13-7	No
Cumene	98-82-8	No
Benzene	71-43-2	No

(United Nations) - Kyoto Protocol - Convention on Climate Change - Greenhouse Gases (GHGs):

Chemical Name	CAS No	(United Nations) - Kyoto Protocol - Convention on Climate Change - Greenhouse Gases (GHGs)
Xylene	1330-20-7	No
Solvent naphtha (petroleum), heavy aliph.	64742-96-7	Νο
Distillates (petroleum), hydrotreated light	64742-47-8	Νο
Stoddard solvent	Mixture	No
Ethyl benzene	100-41-4	No
Petroleum hydrocarbon	64742-47-8	No
Organic oil	8002-09-3	Νο

Product Identifier: Skid[™] Penetrating Lubricant Stock Number: B790 Date of the latest revision of the safety data sheet: 09-05-2022 Supercedes:

Trimethylbenzene 1,2,4-	95-63-6	No
Naphthalene	91-20-3	No
Trimethybenzene	25551-13-7	No
Cumene	98-82-8	No
Benzene	71-43-2	No

Montreal Protocol on Substances that Deplete the Ozone Layer:

Chemical Name	CAS No	Montreal Protocol on Substances that Deplete the Ozone Layer
Xylene	1330-20-7	No
Solvent naphtha	64742-96-7	No
(petroleum), heavy aliph.	01712 507	
Distillates (petroleum),	64742-47-8	Νο
hydrotreated light	04742-47-0	NO
Stoddard solvent	Mixture	No
Ethyl benzene	100-41-4	No
Petroleum hydrocarbon	64742-47-8	No
Organic oil	8002-09-3	Νο
Trimethylbenzene 1,2,4-	95-63-6	No
Naphthalene	91-20-3	No
Trimethybenzene	25551-13-7	No
Cumene	98-82-8	No
Benzene	71-43-2	No

Basel Convention on the Control of Transboundary Movements of Hazardous Wastes and their Disposal.:

Chemical Name	CAS No	Basel Convention on the Control of Transboundary Movements of Hazardous Wastes and their Disposal.
Xylene	1330-20-7	No
Solvent naphtha (petroleum), heavy aliph.	64742-96-7	No
Distillates (petroleum), hydrotreated light	64742-47-8	No
Stoddard solvent	Mixture	No
Ethyl benzene	100-41-4	No
Petroleum hydrocarbon	64742-47-8	No
Organic oil	8002-09-3	No
Trimethylbenzene 1,2,4-	95-63-6	No

Product Identifier: Skid[™] Penetrating Lubricant Stock Number: B790 Date of the latest revision of the safety data sheet: 09-05-2022 Supercedes:

Naphthalene	91-20-3	No
Trimethybenzene	25551-13-7	No
Cumene	98-82-8	No
Benzene	71-43-2	No

16 Other information

Date of the latest revision of the safety data sheet: Revision Number:	09-05-2022
Reason for revision:	Activated by Document Formulation Generation
Other Information:	SDS Prepared by L. Dean Swartz, SDS Coordinator
other mormation.	SDS Trepared by E. Dean Swartz, SDS Coordinator
Disclaimer:	IMPORTANT: WHILE THE DESCRIPTIONS, DATA AND INFORMATION
	CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO
	BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE
	MANY FACTORS MAY AFFECT PROCESSINGOR APPLICATION/USE, WE
	RECOMMEND THAT YOU PERFORM AN ASSESSMENT TO DETERMINE THE
	SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO
	USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED,
	INCLUDING FITNESS FOR A PARTICULAR PURPOSE, ARE MADE
	REGARDING PRODUCTS DESCRIBED, DATA ORINFORMATION SET FORTH.
	IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, OR DATA
	PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF
	SALE. FURTHER, THE DESCRIPTIONS, DATAAND INFORMATION
	FURNISHED HEREUNDER ARE GIVEN GRATIS. NO OBLIGATION OR
	LIABILITY FOR THE DESCRIPTION, DATAAND INFORMATION GIVEN ARE
	ASSUMED. ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.