



Prices Subject to Change Without Notice • While Supplies Last • Some Items May Require Minimum Quantities

FEATURED PRODUCTS

IMPACT WRENCHES



IR-W9691-K4E
1" CORDLESS IMPACT WRENCH (WITH 6" EXTENDED ANVIL)
1" 20V Cordless Impact Wrench 4 Battery Kit with 6" Extended Anvil • Best-in-class power-to-weight ratio • 3,000 ft-lbs of nut busting torque, 2,200 ft-lbs of tightening torque • Friction Ring-Thru-hole Retainer • D-Handle



IR-231HA-2
1/2" SD IMPACT WRENCH
1/2" Air Impact Wrench with 2" Extended Anvil • Super Duty • 600 ft-lb Torque • 8000 RPM • Friction Ring Retainer • Pistol • This impact wrench is tough enough to handle harsh environments, repeated drops and run-ins with any number of chemicals

IMPACT SOCKET SETS & LUG NUT REMOVERS



PREM-9152
10 Piece 1" Drive Truck Wheel Impact Socket Set • Standard: 7/8", 15/16", 1", 1-13/16"; Deep: 33 mm; Thin Wall Deep: 1-1/16", 1-1/8", 1-1/4"; Deep Budd: 1-1/2"; Square: 13/16"



PREM-9153
10 Piece 1" Drive Standard and Deep Length Impact Socket Set • Deep: 33 mm, 35 mm, 41 mm; Deep Budd: 1-1/2"; Thin Wall Deep: 1-1/16", 1-1/8", 1-1/4"; Square: 13/16", 17 mm, 21 mm



PREM-1511TP
11 Piece 1/2" Drive Extra Thin Wall Protector Impact Sockets • Fractional Sizes: 3/4", 13/16", 7/8", 15/16", 1", 1-1/16"; Metric Sizes: 17 mm, 19 mm, 21 mm, 22 mm, 23 mm



PREM-1312D
13 Piece 1/2" Drive Deep SAE Impact Socket Set • Sizes: 7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 13/16", 7/8", 15/16", 1", 1-1/16", 1-1/8", 1-1/4"

2300K
12 Piece Passenger and Light Truck Wheel Lug Nut Removers • Use when key not available • Also removes damaged lug nuts • Tapered left-hand thread grips tapered or straight threads • Also works on hex nuts • Use with 1/2" drive impact wrench • Comes with carrying case • Sizes: #5 (1/2"), #6 (9/16"), #7 (5/8"), #8 (5/8"), #9 (11/16"), #10 (3/4"), #11 (3/4"), #12 (13/16"), #13 (13/16"), #14 (7/8"), #16 (15/16" and 1"), and #18 (1" and 1-1/16")

TORQUE WRENCHES




C3FR250F
1/2" Drive Split-beam Click Wrench • Flex Ratchet • Range: 40-250 ft-lb • 5 ft-lb Increments



C4D600F
3/4" Drive Split-beam Torque Wrench with flex ratchet head • Range 200-600 ft-lb

PERFECT ADHESIVE STEEL WHEEL WEIGHTS



Code	Description	Price
200576FE	1/4 oz Segments • 3 oz Strips • 48 Strips • 576 segments per box • Pre-Taped Steel Adhesive NEW Low Profile Design	
200576FER	1/4 oz Segments • Roll, 11 lbs • 704 segments • Pre-Taped Steel Adhesive NEW Low Profile Design	
300224FE	1/2 oz Segments • 4 oz Strips • 28 Strips • 224 segments per box • Pre-Taped Steel Adhesive NEW Low Profile Design	



44011
StickPro Wheel Cleaning Spray • 22oz bottle • Made for removing residue from adhesive wheel weights



2-RCT
Adhesive Wheel Weight Removal Tool • Chisel shaped end • High impact plastic • Gentle treatment of aluminum and alloy wheels • Non-marking, leaves no damage on metal, paint or glass • Removes stick-on weights, decals, gaskets and more • Secure grip with protective ring for comfortable handling

TIRE LUBRICANTS & ACCESSORIES




PREMA TIRE LUBRICANT: READY TO USE OR CONCENTRATED



Code	Description	Price
PTL-1G	Prema Liquid Blue Ready to Use Tire Lubricant • 1G	
PTLC-1G	Prema Liquid Blue Concentrated Tire Lubricant • Mix Ratio 1:1 to 3:1 • 1 G	



NITRILE GLOVES
Orange, extra thick, diamond textured, powder free • Fits either hand • 100 per box • 8 mm thickness • Available sizes: Medium - **GWON-MD**, Large - **GWON-LG**, X-Large - **GWON-XL**, XX-Large - **GWON-2XL**




2-964
14-1/2" Cotton Tire Swab



2-965
11-1/2" Cotton Tire Swab

COLD WEATHER LUBRICANTS




1515-25
Premier Performance Green Lube Tire and Tube Mounting Compound • Does not change viscosity in warm or cold conditions • Will hold a gel consistency down to -25° • 25 lbs




4444-5
Premier Performance Black Slip Rim Rust Retardant and Tire Mounting Lubricant • Ideal for aluminum and steel wheels and rims • 5 lbs




4444-25
Premier Performance Black Slip Rim Rust Retardant and Tire Mounting Lubricant • Ideal for aluminum and steel wheels and rims • 25 lbs



TIRE CHANGER LUBE BUCKET
LB106259
Straight Head, Coats Rim Clamp Style



Find your local distributor at www.premacanada.ca
1-800-268-6311



Find your local distributor at www.premacanada.ca
1-800-268-6311



TIRE REPAIRS, TOOLS AND ACCESSORIES



PREMA Hybrid Universal Square Repair • Combines the best of both Soft Gum and Hard Gum Technologies • Designed for repairing nail hole injuries in tubeless bias and radial tires in the crown area only • Install with Prema Ultra Fast Dry Vulcanizing Cement

Code	Size	Qty	Price
PUSF-2	W 1-3/4" x L 1-3/4"	100 / box	
PUSF-3	W 2-1/4" x L 2-1/4"	100 / box	
PUSF-3T	W 2-1/4" x L 2-1/4"	200 / box	

2-933
SCRAPER

Innerliner Tire
Scraper



2-936
STITCHER

1/8" x 1-1/2" Plastic
Handled Tire Repair
Stitcher • Corrugated Wheel



PFC-8
PREMA Ultra Fast Dry
Vulcanizing Cement •
Brush Top Can • 8 oz



SNAP-IN TUBELESS VALVES



EHA-413-100
Length 1-1/4" • .453
Valve Hole • TR413



EHA-414-100
Length 1-1/2" • .453
Valve Hole • TR414



EHA-418-100
Length 2" • .453
Valve Hole • TR418



EHA-600HP
Length 1-1/4" • .453
Valve Hole • TR600HP

SCREW-ON VALVE CAPS



**33-0709
ALLIGATOR V2B METAL DOUBLE
SEALING SCREW-ON VALVE CAPS**
Doesn't need to be removed to check air pressure or add air — gauging and inflating is done directly through the valve cap • Has two built-in heat-resistant grommets that prevent loss of air pressure even when the valve core is damaged or dirty • Air pressure check time is reduced by up to 65% • Fits all standard valves • Water and dirt repellent design • Heavy duty all-metal housing



MH-30
Flat Mate Handheld Digital Tire Inflator / Gauge • 174 psi • 6' Hose • Inflate or deflate your tires up to 174 psi with your portable manual inflator • One single handle will inflate and deflate your tires • 4 measurement units (psi, bar, kPa, kg/cm2)



1991
Eurodainu Gauge - Michelin Type • Dial Type Air Line Service Gauge • Use When High Visibility, Accuracy and Durability are Important Factors • Calibrated 10-170 PSI and 0.7-12 Bar • 2 Lb Increments • Includes a 5' Hose and a Euro Style Clip-On Chuck



MW-60-4WAY
4-Way Automatic Tire Inflator • 145 PSI x 4 Outlets • Measures Air Pressure with 4 types of measurements: kPa, BAR, PSI and kg/cm2 • Pre-drilled holes for wall mount or mount to a tire cage with the use of a MW Stand Bracket • 110V with 1/4 Air Inlet

TIRE STUDS AND TOOLS

iGRIP

SCREW IN SHOULDER STUDS



Code	Size	Qty	Price
SS-11100	11 mm	100	
SS-111000	11 mm	1000	
SS-11150	11 mm	150	
SS-11200	11 mm	200	
SS-1124	11 mm	24	
SS-15100	15 mm	100	
SS-151000	15 mm	1000	
SS-15150	15 mm	150	
SS-15200	15 mm	200	
SS-18100	18 mm	100	
SS-181000	18 mm	1000	
SS-18150	18 mm	150	
SS-18200	18 mm	200	
SS-25100	25 mm	100	
SS-251000	25 mm	1000	
SS-25200	25 mm	200	
SS-30100	30 mm	100	
SS-301000	30 mm	1000	
SS-30200	30 mm	200	
SS-401000	40 mm	1000	



SS-181518
Shoulder Stud Tool • 15 mm, 18 mm




SS-302530
Shoulder Stud Tool • 25 mm, 30 mm



SS-321106
Shoulder Stud Tool • 11 mm, 28 mm, 32 mm

STANDARD TRUCK WHEEL GUARDS



60101-5902

Code	Diameter	Holes	Stud Diameter	Price
60101-5902	11-1/4"	10	3/4"	
60102-5903	285 mm	10	22 mm	
60105-7902	275 mm	8	20 mm	

STEERING WHEEL COVERS



3-SWC-500
Double Band Steering Wheel Covers, 24" (500 pack) • Clear, low density plastic • Cloth band • Protects steering wheels from grease and other dirt • Elastic design is easier to apply and remove than stretch wrap covers

CRIBBING & JACKS



AME-15255
AME Cribbing Blocks are certified and tested • Multiple sizes and shapes • Interlocking or aggressive non-slip surface • Non-conducting plastic resists oil and most chemicals • Does not splinter like wood • Made from 100% recycled plastic • 10 piece industrial cribbing block set • Includes: (6) 15230 lanyard colour blue, (3) 15210 lanyard colour yellow and (1) 14465



AME-14140
Titan 22 Ton A/H Service Jack • Extension Saddles include: 1 of each, 1", 2", and 4" • Operates with only 80 PSI of air pressure • Min Height 8.27" • Max Height 20.67" • Stroke 6" • Weight 110 lbs



GT-G432020
Winntec 20 Ton Capacity Jack is among the toughest in the market • Equipped with an air regulator to ensure a long service life • Chrome Ram, Welded Base and Return Springs • Cap 20 T • Min. Height 10" • Max. Height 18.5" • Weight 38 lbs

TIRE CART



MTC
Tire Rider Tuff Tire Cart • Toughest tire cart on the market with its 550 lb loading capacity • Carry 8 tire/wheel assemblies of up to 35" OD • Rubber wheels are solid and flat free