
## **JACKS & STANDS**

## AME-14460



## AME-14455

JackZilla 20T Air/Hydraulic Bottle Jack • Max. Height 18.5" • Min. Height 9.7" • Features an In-Line Regulator to limit air pressure to 94 PSI to prevent air bypass • Built with Flexzilla Whip Hose for maximum durability in all climate conditions • Includes an AME-14453 10" X 10" Jack Plate for optimal weight displacement on uneven or non-compacted



and Wheel Service Solutions

#### AME-14401

40T Pinned Jack Stands with wheels and an extension handle - 1 Pair. Sturdy, welded steel construction for superior safety and strength • Capacity is 20T per stand • Min Height 13" • Max Height 20"



## GT-G420250

Winntec 2 Ton Compact Turbo Lift Jack • Built with quality materials and loaded with features to increase durability and efficiency . Professional universal joint release • Handle protector • Min. height 2.95" • Max. height 20.08" • Length 27.01" • Width 13.5" • Gross weight 74.96 lbs



## GT-G420303

Winntec 3 Ton Turbo Floor Garage Jack • Built with quality materials and loaded with features • Professional universal joint release • Handle protector • Min. height 5.12" • Max. height 19.29" • Length 31.30" • Width 15.16" • Gross weight 94.7 lbs



### GT-G432024

Winntec 24 Ton Single Stage A/H Jack • Comes equipped with an extension screw, individual extension pegs, and heavy duty wheels designed for daily use • Min. height 8.46" • Max. height 21.35" • Stroke 5.55" • Gross weight 92.59 lbs



## **INFLATORS, TOOLS & GAUGES**

Find your local distributor at www.premacanada.ca

1-800-268-6311


## **MW-60-4WAY**

4-Way Automatic Tire Inflator • 145 PSI x 4 Outlets • Measures Air Pressure with 4 types of measurements: kPa, bar, PSI and kg/cm2 • Pre-drilled holes for wall mount or mount to a tire cage with the use of a MW Stand Bracket 110V with 1/4 Air Inlet



Eurodainu Gauge - Michelin Type · Dial Type Air Line Service Gauge

 Use when high visibility, accuracy and durability are important factors • Calibrated 10-170 PSI and 0.7-12 bar • 2 lb increments • Includes a 5' Hose and



## 25008

3-in-1 Quick Inflator & Valve Core Extractor Tool • Features Valve Core Installation, Valve Core Removal, and Quick Tire Inflation • Max. Inflation Pressure: 160 PSI / 11 bar • Ensures you don't lose the valve core or air in the tire during the process • \*Special Order item



#### 5410

Snap-In Valve Stem Puller/Remover with Built-In Rim Protector • Innovative material protects rims and won't mark • Double fulcrum point ensures center-seating of valve stems for proper sealing to the rim • Ergonomically designed to lower installation force required • Extreme durability for long life



## 1991-HS&CK

Replacement Hose and Chuck for 1991 Eurodainu Gauge - Michelin Type • Also includes the special Euro fitting to go into the gauge body

## 5127

Colour Coded Tread Depth Gauge with Metal Indicator Bar • Shows Red - Yellow Green • 0 - 32 in 32nd increments

# AIR TOOLS





**BUY THE** IR-285B-6

AND **RECEIVE AN IR-327LS-A AND AN** 

**IR-SK8C5TN** FREE!

#### IR-285B-6

1" Air Impact Wrench with 6" Extended Anvil • Heavy Duty • 1475 ft-lb Torque • Friction Ring-Thru-hole Retainer • D-handle Inside Trigger

### IR-327LS-A

Ingersoll Rand Air Tire Buffer, 7/16" Hex Quick Change, .5HP, 3,000 RPM

1" Drive SAE Deep Truck Service Impact Socket Set • 5 sockets (13/16" square; 33 mm & 1-1/2" deep hex; 1-1/8" and 1-1/4" deep thin wall hex) and blow-molded case



AIR-6345

Aircat Decal/Pinstripe Removal Tool • 2,600 RPM • 0.6 HP Motor • Built-in gear reduction for added power and added stall resistance • Spindle lock feature for easy accessory change • Ergonomic composite over mold grip provides comfort • 2.15 lbs

PNEUMATIG TOOLS



### AIR-6402

Aircat Low Speed Composite Tire Buffer • 2,600 RPM • Stall resistant 0.60 HP motor • Throttle lever design Coaxial rear hose assembly to eliminate blowing of rubber particles/ dust in the work area • 5/16" hex quick change chuck with threaded arbor for mounting buffing cones and accessories • 2.2 lbs



## AIR-1992-A

Aircat 1" Straight Impact Wrench with 6" Extended Anvil • Provides 1,800 ft-lb maximum torque and 2,000 ft-lb of loosening torque • 5,000 RPM • Low maintenance pin-less hammer provides ultimate reliability and added hitting power • 27.8 lbs

## **REPLACEMENT RUBBER VALVES**

Code / Valve Base		Description			
PREM-207	0	Replacement Snap-In Valve for Schrader GM, Ford and Programmable Sensors			
PREM-208	$\bigcirc$	Replacement Clip Design Snap-In Valve for the 5775 Dodge Dart Sensor and Redi-Sensor			
PREM-210	0	Replacement Snap-In Valve for certain Schrader sensors on Ford, GM, and Subaru Vehicles between 2015 - 2024			
PREM-211	0	Replacement Snap-In Valve for Dodge Ram Models • Base has 4 square sides			
PREM-215A	0	Replacement Snap-In Valve for Smart Sensor			
20018	0	TPMS Snap-in Service Kit (Ford/GM) • Interchangeable with EZ-Sensor or U-Pro			























Tire

## **ORANGE NITRILE GLOVES, 8 mil**

Extra strength 8 mil GRIP powder-free orange nitrile gloves provide maximum protection, performance, and durability.

Latex-free, these gloves offer great chemical resistance in addition to superior puncture and abrasion resistance • 100 gloves per box, 50 pairs per box • Touchscreen compatible

Code	Size	Price
FG-OR7101-SM	Small	
FG-OR7102-MD	Medium	
FG-OR7103-LG	Large	
FG-OR7104-XL	Extra Large	
FG-OR7105-2XL	Extra Extra Large	

## **KEX COMBI REPAIRS AND CEMENT**

Kex Combi Repair Units with Pilot Wire • Install with KX-511F Flammable Chemical Cement • Use in conjunction with PCC-1, PCC-2 and PCC-4 Carbide Cutters



Code	Injury Size	Qty / Box	Price
KX-386	1/8"	24	
KX-387	1/4"	25	
KX-388	3/8"	25	



### KX-511F

Kex Super Fast Dry Vulcanizing Cement • Use with all Kex Patches and Plugs • 8 oz

## **CORDLESS TIRE BUFFER**



### IR-G4911-K1

20V Cordless Tire Buffer, 7/16" Hex Quick Change, 3000 RPM • Kit includes 1 - 4911 Cordless 20V Tire Buffer, 1 - BL2012 20V 2.5Ah Battery and 1 -BC1121 Single Bay Charger • Pneumatic has met its match. Introducing the world's first 20V tire buffer – the G4911 Cordless Tire Buffer from Ingersoll Rand® • Capable of 45 repairs on a single 2.5Ah battery, the G4911 makes tire repair easy - whether it's quick work on passenger vehicles or tackling tough repairs on heavy equipment • The patent-pending compact IQV20™ cordless design with angled battery interface provides greater tool accessibility inside small tires without the maneuverability restrictions of an air hose • 2.78 lbs with battery

## **COUNTERACT BALANCING COMPOUND**



Code	Size	Price
CAB01	1 oz. Bag	
CAB02	2 oz. Bag	
CAB03	3 oz. Bag	
CAB04	4 oz. Bag	
CAB05	5 oz. Bag	
CAB06	6 oz. Bag	
CAB08	8 oz. Bag	
CAB10	10 oz. Bag	
CAB12	12 oz. Bag	
CAB14	14 oz. Bag	
CAB16	16 oz. Bag	

## **TORQUE CHART**



## TG-22

Coated paper 22" x 34" lug nut torque chart • Provides proper torque settings for more than 500 cars & light trucks 1990-2025

## **TIRE AND WHEEL CLEANERS**

## MTY-DL3100-1

Mighty VS7® Non-Acid Tire & Wheel Cleaner is a revolutionary formula allowing a thick, gel-like cleaner to cling to the surface, aggressively removing even the toughest brake dust, dirt & grime • 1 gal



## MTY-DL3101-1

Mighty VS7® Presto Whitewall Tire Cleaner is a water-based formula that removes factory coating including tire blue, curb burns, dirt, and stains. Dilute up to 1:6 • 1 gal



### MTY-DL3102-1

Mighty VS7® Wheel Acid Tire & Wheel Cleaner is a powerful acid-based formula • Use on wire wheels, chrome, and alloys • Instantly removes road film, oxidized metals. and brake cleaner • 1 gal

## **HAND CLEANER**

#### **PHC-SUPER**

Prema Heavy Duty Hand Cleaner • Superior cleaning ability for hard to remove dirt and grime • Gentle to the skin • Suitable for daily use • Does not clog drains • 5 L



## **PHC-DISP**

Prema Hand Soap Dispenser

## **HEAVY DUTY ALUMINUM ALLOY** TRUCK AXLE SHIMS





Code	Description	<b>Price</b> Boxes of 6
10705	Width - 4.0"   Degree - 0.5°   Length - 6.5"	
10712	Width - 4.0"   Degree - 1.0°   Length - 6.5"	
10722	Width - 4.0"   Degree - 1.5°   Length - 6.5"	
10732	Width - 4.0"   Degree - 2.0°   Length - 6.5"	
10742	Width - 4.0"   Degree - 2.5°   Length - 6.5"	
10752	Width - 4.0"   Degree - 3.0°   Length - 6.5"	

## **TIRE CHANGER ACCESSORIES**

	Code	Description	Price		Code	Description	Price
	TC247G15A-10	Nylon long arm inserts for steel mount/ demount head • 10 pack • Yellow		•	4-103502B	Hunter nylon insert • Yellow	
5	TI182961	Coats type mount/ demount head plastic insert • 2 pack • White			J54-1300014	Corghi Proline 124 Tire Changer • Steel mount/demount head protective plastic insert • 10-Pack • Yellow	
	444-80106	Corghi mount/demount body insert • 10 pack • Mondolfo compatible: AS912, AS914, AS944 • Yellow			J4-103502K	Protective Head Insert, yellow (x10) • Protective Tail Insert, yellow (x10) • Screws (x4)	
	444-80107	Corghi mount/demount tail insert • 5 pack • Banana shaped piece • Mondolfo compatible: AS912, AS914, AS944 • Yellow		0	4-133385A	Insert used in leverless head of RAPTOR tire changer • V3 • 5 pack • Grey	









and Wheel

Service

Solutions